

PLC & PC Control		
DL205 PLC Units		
Product Code	DL205 CPUs	Aust\$
H2-DM1	Do-more H2 series PLC CPU module, 192k words total (64k words ladder (flash memory), 128k words user data memory (SRAM with battery backup)). Ladder programming, real time clock/calendar, two built-in communications ports: (1) RS-232 port supports programming, K-sequence slave, MODBUS RTU master/slave and ASCII IN/OUT; (1) USB port supports programming. Supports bumpless run-time editing and 2000 PID loops. Battery included. Requires Do-more Designer programming software (free download online). User manual H2-DM-M available as a free download, or purchase hard copy separately.	\$689
H2-DM1E	Do-more H2 series PLC CPU module, 192k words total (64k words ladder (flash memory), 128k words user data memory (SRAM with battery backup)). Ladder programming, real time clock/calendar, three built-in communications ports: (1) RS-232 port supports programming, K-sequence slave, MODBUS RTU master/slave and ASCII IN/OUT; (1) USB port supports programming; (1) Ethernet port supports programming, TCP/IP, UDP/IP and Modbus/TCP. Supports bumpless run-time editing and 2000 PID loops. Battery included. Requires Do-more Designer programming software (free download online). User manual H2-DM-M available as a free download, or purchase hard copy separately.	\$765
D2-262	DL205 CPU, 15.8k words ladder memory, (1) RS-232 (RJ12) and (1) RS-232/RS-422/RS-485 (DB15HD female) port(s). Purchase D2-BAT-1 backup battery separately. Requires DirectSoft Programming Software v6.3 or later.	\$655
Product Code	DL205 I/O Bases	Aust\$
D2-03B-1	3-slot base, 110-220 VAC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-03B	\$281
D2-03BDC1-1	3-slot base, 12-24 VDC input power, no isolated auxiliary output, local I/O expandable, replaces D2-03BDC-1	\$325
D2-04B-1	4-slot base, 110-220 VAC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-04B	\$305
D2-04BDC1-1	4-slot base, 12-24 VDC input power, no isolated auxiliary output, local I/O expandable, replaces D2-04BDC-1	\$358
D2-06B-1	6-slot base, 110-220 VAC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-06B	\$379
D2-06BDC1-1	6-slot base, 12-24 VDC input power, no isolated auxiliary output, local I/O expandable, replaces D2-06BDC-1	\$424
D2-06BDC2-1	6-slot base, 125 VDC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-06BDC-2	\$435
D2-09B-1	9-slot base, 110-220 VAC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-09B	\$455
D2-09BDC1-1	9-slot base, 12-24 VDC input power, no isolated auxiliary output, local I/O expandable, replaces D2-09BDC-1	\$504
D2-09BDC2-1	9-slot base, 125 VDC input power, 24 VDC 300mA isolated auxiliary output, local I/O expandable, replaces D2-09BDC-2	\$534
Product Code	DL205 DC and AC Input Modules	Aust\$
D2-08ND3	8-point 12-24 VDC current sinking/sourcing input module, 1 common (2 common terminals), removable terminal	\$132
D2-16ND3-2	16-point 24 VDC current sinking/sourcing input module, 2 commons (isolated), European type removable terminal	\$215
D2-32ND3	32-point 24VDC current sinking/sourcing input module, 4 commons (isolated). <b>Requires pre-wired ZIPLink connector cable and terminal block for this I/O Module.</b> The part number is ZL-D24-CBL40#, where # designates either 0.5, 1, or 2 meter cable lengths. Terminal block module for ZL-D24-CBL40# cable is part number ZL-RTB40 or ZL-LTB32-24. (Or build a custom cable with ZL-D24-CON-R, ZL-D24-CON-X, ZL-D24-CON or ZL-D24-CBL40#P.)	\$303
D2-32ND3-2	32-point 5-15 VDC current sinking/sourcing input module, 4 commons (isolated). <b>Requires pre-wired ZIPLink connector cable and terminal block for this I/O Module.</b> The part number is ZL-D24-CBL40# where # designates either 0.5, 1, or 2 meter cable lengths. Terminal block module for ZL-D24-CBL40# cable is part number ZL-RTB40 or ZL-LTB32-24. (Or build a custom cable with ZL-D24-CON-R, ZL-D24-CON-X, ZL-D24-CON or ZL-D24-CBL40#P.)	\$303
D2-08NA-1	8-point 110 VAC input module, 1 common (2 common terminals), removable terminal	\$196
D2-08NA-2	8-point 220 VAC input module, 1 common (2 common terminals), removable terminal	\$239
D2-16NA	16-point 110 VAC input module, 2 commons (isolated), European type removable terminal	\$327

Product Code	DL205 DC and AC Output Modules	Aust\$
D2-04TD1	4-point 12-24 VDC current sinking output module, 1 common (4 common terminals), 4.0A/point, 8.0A/module, fused per point (non-replaceable), removeable terminal	\$159
D2-08TD1	8-point 12-24 VDC current sinking output module, 1 common (2 common terminals), 0.3A/point, 2.4A/module, fused per common (non-replaceable), removable terminal	\$136
D2-08TD2	8-point 12-24 VDC current sourcing output module, 1 common (2 common terminals), 0.3A/point, 2.4A/module, fused per common (non-replaceable), removable terminal	\$136
D2-16TD1-2	16-point 12-24 VDC current sinking output module, 1 common (2 common terminals), 0.1A/point, 1.6A/module, no fuse, European type removable terminal	\$233
D2-16TD2-2	16-point 12-24 VDC current sourcing output module, 1 common (2 common terminals), 0.1A/point, 1.6A/module, no fuse, European type removable terminal	\$233
F2-16TD1P	16-point, 12-24 VDC current sinking output module, 2 common terminals, 0.25A/point continuous, overcurrent trip 0.6A min, 1.2A max, independent overtemperature protection for each output, removable terminal block	\$193
F2-16TD2P	16-point, 12-24 VDC current sourcing output module, 1 common terminal, 0.25A/point continuous, overcurrent trip 0.6A min, 1.2A max, independent overtemperature protection for each output, removable terminal block	\$193
D2-32TD1	32-point 12-24 VDC current sinking output module, 4 commons (isolated), 0.1A/point, 3.2A/module, no fuse. <b>Requires pre-wired ZIPLink connector cable and terminal block for this I/O Module.</b> The part number is ZL-D24-CBL40# where # designates either 0.5, 1, or 2 meter cable lengths. Terminal block module for ZL-D24-CBL40# cable is part number ZL-RTB40, or ZL-RFU40. (Or build a custom cable with ZL-D24-CON-R, ZL-D24-CON-X, ZL-D24-CON or ZL-D24-CBL40#P.)	\$303
D2-32TD2	32-point 12-24 VDC current sourcing output module, 4 commons (isolated), 0.1A/point, 3.2A/module, no fuse. <b>Requires pre-wired ZIPLink connector cable and terminal block for this I/O Module.</b> The part number is ZL-D24-CBL40# where # designates either 0.5, 1, or 2 meter cable lengths. Terminal block module for ZL-D24-CBL40# cable is part number ZL-RTB40, or ZL-RFU40. (Or build a custom cable with ZL-D24-CON-R, ZL-D24-CON-X, ZL-D24-CON or ZL-D24-CBL40#P.)	\$303
D2-08TA	8-point 18-220 VAC output module, 1 common (2 common terminals), 0.5A/point, 4.0A/module, replaceable fuse, removable terminal	\$259
F2-08TA	8-point 24-140 VAC high current output module, 2 commons (isolated), 1.5A/point, 4.0A/common, removable terminal	\$232
D2-12TA	12-point 18-110 VAC output module 2 commons (isolated), 0.3A/point, 1.8A/common, replaceable fuse, European type removable terminal	\$317
D2-04TRS	4-point 5-30 VDC or 5-240 VAC isolated relay output module, 4 Form A (SPST) relays, 4 commons, 4A/point, 8.0A/module, replaceable fuse, removable terminal	\$164
D2-08TR	8-point 5-30 VDC or 5-240 VAC relay output module, 8 Form A (SPST) relays, 1 common (2 common terminals), 1A/point, 4.0A/module, replaceable fuse, removable terminal	\$160
F2-08TR	8-point 12-28 VDC or 12-250 VAC relay output module, 8 Form A (SPST) relays, 2 isolated commons, 10A/common max., no fuses, removable terminal	\$154
F2-08TRS	8-point 12-28 VDC or 12-240 VAC relay output module, 5 Form A (SPST) relays, 3 Form C (SPDT) relays, 8 isolated commons, 7A/point max., no fuses, removable terminal	\$187
D2-12TR	12-point 5-30 VDC or 5-240 VAC relay output module, 12 Form A (SPST) relays, 2 commons, 1.5A/point max., 3.0A/common, 2 replaceable fuses, removable terminal	\$259
D2-08CDR	4-point 24 VDC sinking/sourcing input, 1 common, 4-point relay output, 1A/pt., 4A/module, 1 common, replaceable fuse	\$164
Product Code	DL205 Analogue Modules	Aust\$
F2-04AD-1	4-channel analog input module, 12 bit resolution, range: 4-20mA.	\$369
F2-04AD-2	4-channel analog input module, 12 bit resolution, range: 0-5V, 0-10V, -5 to +5V, -10 to +10V.	\$381
F2-08AD-1	8-channel analog input module, 12 bit resolution, range: 4-20mA.	\$428
F2-08AD-2	8-channel analog input module, 12 bit resolution, ranges: 0-5 VDC, 0-10 VDC, -5 to +5V, -10 to +10VDC.	\$479
F2-02DA-1	2-channel analog output module, 12 bit resolution, range 4-20mA.	\$292
F2-02DA-2	2-channel analog output module, 12 bit resolution, ranges: 0-5V, 0-10V, -5 to +5V, -10 to +10V.	\$305
F2-02DAS-1	2-channel analog output, 16 bit resolution, isolated, range: 4-20mA current sourcing.	\$408
F2-02DAS-2	2-channel analog output, 16 bit resolution, isolated, range: 0-5V, 0-10V.	\$462
F2-08DA-1	8-channel analog output module, 12 bit resolution, range: 4-20mA, sink or source output configurable. Designed to operate with 24 VDC user-supplied power supply.	\$528
F2-08DA-2	8-channel analog output module, 12 bit resolution, ranges: 0-5V, 0-10V.	\$536

F2-4AD2DA	4-channel analog input and 2 channel analog output module (sink), 12 bit resolution, range 4-20mA.	\$512
F2-8AD4DA-1	8-channel analog input / 4-channel analog output module. Inputs: selectable 16-bit, 14-bit, or 12-bit resolution, range 0-20mA. Outputs: 16-bit resolution, range 4-20mA, current sourcing. Not supported in D2-230 or D2-240 CPUs.	\$633
F2-8AD4DA-2	8-channel analog input / 4-channel analog output module. Inputs: selectable 16-bit, 14-bit, or 12-bit resolution, range 0-5 VDC or 0-10 VDC. Outputs: 0-5 VDC at 15 bit resolution, 0-10 VDC at 16 bit resolution. Not supported in D2-230 or D2-240 CPUs.	\$633

Product Code	DL205 Temperature Input Modules	Aust\$
F2-04RTD	4-channel RTD input module, 0.15 degrees C resolution, supports: Pt100, jPT100, Pt1000, Cu10, Cu25.	\$545
F2-04THM	4-channel thermocouple input module, 0.1 degrees C resolution, supports: J, E, K, R, S, T, B, N, C; 0-5 VDC, -5 to +5 VDC, 0-156 mVDC, -156 to +156 mVDC at 16-bit resolution.	\$545
Product Code	DL205 Expansion Modules	Aust\$
D2-EM	DL205 Local I/O expansion module. Installs on the side of each I/O base, CPU base AND expansion bases, in a local expansion system. Includes 2 RJ-45 cable ports for expansion cables to plug into, single ACTIVE LED for system status indication, TERM toggle switch for last and first base termination. Expansion cables sold separately.	\$167
D2-CM	DL205 Local I/O expansion controller module. Installs in the CPU slot of each expansion base, expansion base number rotary switch selectable, PWR, RUN, and DIAG LEDs for system status indication, compatible with D2-250-1 and D2-260.	\$133
D2-EXCBL-1	DL205 base expansion cable, 3.08 ft. (1m), used with D2-EM expansion modules.	\$29
H2-ERM100	Ethernet Remote Master module, for Ethernet remote I/O on a 10/100Base-T network at 10/100 Megabaud. Must be installed in a local base with a D2-240, D2-250(-1), D2-260, Do-more H2 series or H2-WPLCx-xx CPU module in the CPU slot. Ethernet cable (purchased separately) connects to H2/H4/T1H-EBC(100) modules directly or via Ethernet hub(s). (Not compatible with D2-230 CPU.)	\$534
H2-EBC100	Ethernet Base Controller for DL205 base, for connection to PLC Ethernet master or PC Ethernet network interface card. Supports 10/100Mb auto-detect, TCP/IP, UDP/IP, IPX, and Modbus TCP/IP application layer protocol.	\$758
Product Code	DL205 Communication Modules	Aust\$
D2-DCM	Data Communication Module, master/slave on a DirectNET Network, slave on a Modbus RTU Network, RS232C/RS422 communications, cable not included.	\$794
H2-ECOM100	Ethernet Communication Module for DL205 PLC systems. Supports master slave communication, 10/100Mb auto-detect, TCP/IP, UDP/IP, IPX, and Modbus TCP application layer protocol.	\$649
H2-SERIO	3 Port RS-232 Serial I/O module for PC control with the WinPLC or an EBC-based system connected to a PC. These additional serial ports will allow connection of a wide range of serial devices, such as barcode scanners, scales, printers, modems, etc. Module usage covered in H2-WPLC-M, ordered separately.	\$435
H2-SERIO-4	3-port RS-232/RS-485 Serial I/O module for use with the WinPLC or an H2-EBC100-based system connected to a PC; (2) RS-232 ports, (1) RS-485 port (2-wire or 4-wire). These additional serial ports allow connection of a wide range of serial devices, such as barcode scanners, scales, printers, modems, etc. Module usage documented in H2-WPLC-M, free download or purchase separately.	\$388
Product Code	DL205 Advanced Modules	Aust\$
F2-CP128	3 Port Overdrive CoProcessor module, 128K battery backed RAM, 26Mhz clock. Port 1: RS232C/RS422/RS485 (115.2K baud max.); Port 2: RS232C/RS422/RS485 (57.6K baud max.); Port 3: RS232C, maximum baud 19.2K. Includes CD containing ABM Commander for Windows & DOS and example programs. Also includes a DB9 connector, port 1/3 splitter, and a 7 foot 6P6C cable.	\$721
H2-CTRIO2	High-speed counter interface module for D2-240, D2-250(-1), D2-260 CPU based PLCs, Do-more H2 and T1H series PLCs, and WinPLC. (8) 9-30 VDC sink/source inputs, (4) 5-36 VDC isolated sink/source outputs, 1A per point. Inputs supported: 2 quadrature encoder counters up to 250kHz, or 4 single-channel counters up to 250kHz, and 4 high-speed discrete inputs for Reset, Inhibit, or Capture. Outputs supported: 4 independently configurable high-speed discrete outputs or 2 channels pulse output control, 20Hz-250kHz per channel, pulse and direction or CW/CCW pulses. (Not compatible with D2-230 CPU.) Must use with Do-more Designer or CTRIO Workbench v2.2.0 or higher.	\$766
D2-CTRINT	Counter Interface Module, 4 isolated DC inputs, 1 pulse train output (cw) or 2 pulse train outputs (cw,ccw) with DC input restrictions, accepts two up-counters when used with D2-240, D2-250(-1) or D2-260 (one only with D2-230), or one up/down counter	\$264
F2-08SIM	8-point Input Simulator	\$121
Product Code	DL205 Spare Parts and Accessories	Aust\$
D2-ACC-1	Spare screws for DL205 base power supply terminals (quantity 8) and one plastic terminal strip cover	\$33
D2-ACC-2	Spare screws for DL205 4-point and 8-point I/O module terminal blocks (quantity 16)	\$33
D2-BAT-1	DL06, D2-250(-1), D2-260, D3-350 CPU battery (optional) and replacement battery for the C-more touch panels	\$15
D2-FUSE-1	3.15A slow blow spare fuses for D2-12TA (quantity 5)	\$33
D2-FUSE-3	6.3A slow blow spare fuses for D2-08TA, D2-04TRS, D2-08TR, D2-08CDR (quantity 5)	\$33
D2-FUSE-4	4A fuses for D2-12TR (quantity 5)	\$33
D2-8IOCON	8-point module connectors (quantity 5)	\$77
D2-16IOCON	16-point module connectors (quantity 5)	\$226

D2-IOCVR	I/O module covers (quantity 5)	\$23
D2-BASECVR	DL205 base covers for expansion connector on right side of '-1' bases (quantity 3)	\$17
D2-FILL	Filler Module	\$33

Product Code	DL205 Software & Programming Cables	Aust\$
D2-DSCBL	12 ft. (3.66m) RS-232 shielded PC programming cable for DirectLOGIC DL05, DL06, DL105, DL205, D3-350 and D4-450 CPUs, Do-more H2 series CPUs, and CLICK CPUs. 9-pin D-shell female connector to an RJ12 6P6C connector.	\$32
D2-DSCBL-1	12 ft. (3.66m) RS-232 shielded PC programming cable for DL06, D2-250(-1), D2-260 CPUs and D0-DCM. 9-pin D-shell female connector to a 15-pin male HD15 connector.	\$51
D2-DSCBL-2	12 ft. (3.66m) shielded pigtail cable for port 2 of a DL06, D2-250(-1) or D2-260 CPU. 15-pin D-shell male SVGA connector to 14 tinned wires.	\$62
D3-DSCBL-2	12 ft. (3.66m) RS-232 shielded PC programming cable for the D3-330 and D3-330P CPUs. An RS232 Data Communications Unit is also required to use this cable. 9-pin D-shell female connector to a 25-pin D-shell male connector. Can also be used to connect to the bottom port of a DL405 or D3-350 CPU, or to DL205/DL305/DL405 DCM modules.	\$52
EA-MG-PGM-CBL	6 ft. PC programming cable assembly for C-more micro EA1 series STN panels, CLICK CPUs, DoMore H2 series CPUs, and DirectLogic CPUs with RJ12 programming ports. Assembly includes (1) standard USB A-type connector to B-type connector cable, (1) custom converter, and (1) RS-232C cable with RJ12 modular connector on each end (also sold separately as DV-1000CBL.) (Note: This cable assembly uses the PC's USB port and converts the signals to serial transmissions. The USB port supplies 5 VDC to the Micro-Graphic panel for configuration operations).	\$109
DA-DSCBL	Single kit containing 1 each of: D2-DSCBL, D3-DSCBL-1, D3-DSCBL-2, D4-DSCBL. Saves over the price of cables purchased separately.	\$219
PC-DSOFT6	DirectSOFT 6, Version 6.0 or higher, Windows PC programming and documentation software, programs DL05/06/105/205/305/405 systems. Package includes software CD and manual. Programming cable sold separately.	\$782
PC-DS100	DirectSOFT Windows limited programming and documentation software. <b>Free download only.</b> For use with all DirectLOGIC PLCs.	<b>Free Download</b>
PC-R60-U	DirectSOFT upgrade, Rel 6.0. Allows you to upgrade from a previously purchased DirectSOFT 16 or 32-bit software version. Package includes software CD and manual. Not compatible with any free versions of software. Proof of existing purchased license required. Programming cable sold separately.	\$552
DM-PGMSW	Do-more Designer Windows PC programming and documentation software <b>can be downloaded at no charge.</b> Alternatively a CD copy can be purchased for a nominal charge. No Keycode Required to Activate Software	<b>Free Download</b>
Product Code	ZIPLinks Connector Cables - DL205	Aust\$
ZL-D2-CBL10	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$33
ZL-D2-CBL10-1	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$37
ZL-D2-CBL10-2	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$45
ZL-D2-CBL19	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RRL16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$57
ZL-D2-CBL19-1	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RRL16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$61
ZL-D2-CBL19-2	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RRL16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$69
ZL-D2-CBL19-1P	ZIPLink cable that allows DirectLOGIC 205 PLC I/O modules with 19 terminals to custom wire to third party devices, 24 AWG, 1.0 meter (3.3 ft.) length	\$52
ZL-D2-CBL19-2P	ZIPLink cable that allows DirectLOGIC 205 PLC I/O modules with 19 terminals to custom wire to third party devices, 24 AWG, 2.0 meter (6.6 ft.) length	\$61
ZL-D24-CBL40	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 0.5 meter (1.6 ft.) length	\$43
ZL-D24-CBL40-1	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$51
ZL-D24-CBL40-2	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$67
ZL-D24-CBL40-X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 0.5 meter (1.6 ft.) length	\$66

ZL-D24-CBL40-1X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$74
ZL-D24-CBL40-2X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$90
ZL-D24-CBL40-1P	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 180-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$47
ZL-D24-CBL40-2P	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 180-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$62
ZL-D24-CBL40-1XP	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 45-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$70
ZL-D24-CBL40-2XP	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 45-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$85
ZL-D24-CON-R	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Ribbon cable type connector, package of 2.	\$53
ZL-D24-CON-X	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Solder type connector, 45-degree exit, package of 2.	\$94
ZL-D24-CON	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Solder type connector, 180-degree exit, package of 2.	\$48
ZL-D2-CBL10-1P	ZIPLink PLC cable, allows DirectLOGIC 205 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$33
ZL-D2-CBL10-2P	ZIPLink PLC cable, allows DirectLOGIC 205 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$40