

	PLC & PC Control	
	Ziplinks	
Product Code	DirectLOGIC ZIPLinks Connector and Communication Modules	Aust\$
ZL-CDM-RJ12X10	ZIPLink 10-port communication distribution module, 4 RJ12 ports, and 1 screw terminal port; mounts on 35 mm DIN rail part # DN-R35S1.	\$36
ZL-CDM-RJ12X4	ZIPLink 4-port communication distribution module, 4 RJ12 ports, and 1 screw terminal port; mounts on 35 mm DIN rail part # DN-R35S1	\$28
ZL-CMA15	ZIPLink communications adapter for use with all 15-pin high-density communication ports on all DirectLOGIC PLCs. No signal indication and no surge protection.	\$18
ZL-CMA15L	ZIPLink communications adapter for use with all 15-pin high-density communication ports on all DirectLOGIC PLCs. Signal indication and surge protection included.	\$53
ZL-FUSE-16	ZIPLink reduced-width stand-alone fuse module, 16-point, 5mm x 20mm fuses, 250 VAC/VDC, 8A / circuit, 35mm DIN rail mount. Fuses sold separately.	\$199
ZL-FUSE-H3	ZIPLink fuse, replacement, 3A. Package of 4. For use with ZL-RRL16HDF-24-1 or ZL-RRL16HDF-24-2 fused relay modules.	\$11
ZL-FUSE-H4	ZIPLink fuse, replacement, 4A. Package of 4. For use with ZL-RRL16HDF-24-1 or ZL-RRL16HDF-24-2 fused relay modules.	\$11
ZL-FUSE-H5	ZIPLink fuse, replacement, 5A. Package of 4. For use with ZL-RRL16HDF-24-1 or ZL-RRL16HDF-24-2 fused relay modules.	\$11
ZL-FUSE-H63	ZIPLink fuse, replacement, 6.3A. Package of 4. For use with ZL-RRL16HDF-24-1 or ZL-RRL16HDF-24-2 fused relay modules.	\$11
ZL-LTB16-24-1	ZIPLink sensor input module, 16-point, LED indication, 24 VDC, 35mm DIN rail mount.	\$122
ZL-LTB32-24-1	ZIPLink sensor input module, 32-point, LED indication, 24 VDC, 35mm DIN rail mount.	\$198
ZL-RELAY-120X4	ZIPLink replacement relays for the ZL-RRL16-120, ZL-RLS1-120, and ZL-RLS4-120. 120 VAC coils, package of 4.	\$26
ZL-RELAY-24X4	ZIPLink replacement relays for the ZL-RRL16-24, ZL-RS1-24, and ZL-RS4-24. 24 VDC coils, package of 4.	\$18
ZL-RELAY-F24X4	ZIPLink relay, replacement, 24 VDC (coil), 8A @ 250 VAC, 8A @ 30 VDC. Package of 4. For use with ZL-RRL16F-24-1 and ZL-RRL16F-24-2 relay modules.	\$31
ZL-RELAY-HDF24X4	ZIPLink relay, replacement, 24 VDC (coil), 5A @ 250 VAC, 5A @ 30 VDC. Package of 4. For use with ZL-RRL16HDF-24-1 or ZL-RRL16HDF-24-2 relay modules.	\$33
ZL-RFU20	ZIPLink 16-point fuse module. Mounts on 35 mm DIN rail part # DN-R35S1.	\$141
ZL-RFU40	ZIPLink 32-point fuse module. Mounts on 35 mm DIN rail part # DN-R35S1.	\$233
ZL-RLS1-120	ZIPLink stand alone single relay module, 1 relay in socket, SPST, 120 VAC coil, relay included. Mounts on 35 mm DIN rail part # DN-R35S1. For replacement relay, use ZL-RELAY-120X4.	\$32
ZL-RLS1-24	ZIPLink stand alone single relay module, 1 relay in socket, SPST, 24 VDC coil, relay included. Mounts on 35 mm DIN rail part # DN-R35S1. For replacement relay, use ZL-RELAY-24X4.	\$30
ZL-RLS4-120	ZIPLink stand alone four relay module, 4 relays in sockets, SPST, 120 VAC coils, relays included. Mounts on 35 mm DIN rail part # DN-R35S1. For replacement relays, use ZL-RELAY-120X4.	\$97
ZL-RLS4-24	ZIPLink stand alone four relay module, 4 relays in sockets, SPST, 24 VDC coils, relays included. Mounts on 35 mm DIN rail part # DN-R35S1. For replacement relays, use ZL-RELAY-24X4.	\$84
ZL-RRL16-24-1	ZIPLink 16-relay output module, sinking, 24VDC coils, LED indication on each relay coil, SPDT socketed relays included. Mounts on 35mm DIN rail part # DN-R35S1. For replacement relays, use ZL-RELAY-24X4.	\$203
ZL-RRL16-24-2	ZIPLink 16-relay output module, sourcing, 24VDC coils, LED indication on each relay coil, SPDT socketed relays included. Mounts on 35mm DIN rail part # DN-R35S1. For replacement relays, use ZL-RELAY-24X4.	\$203
ZL-RRL16F-24-1	ZIPLink fused relay module, 16-point, sinking, SPDT socketed relays (included), LED indication, 24 VDC (coil), 8A @ 250 VAC, 8A @ 30 VDC, 35mm DIN rail mount. Fuses sold separately.	\$392
ZL-RRL16F-24-2	ZIPLink fused relay module, 16-point, sourcing, SPDT socketed relays (included), LED indication, 24 VDC (coil), 8A @ 250 VAC, 8A @ 30 VDC, 35mm DIN rail mount. Fuses sold separately.	\$392
ZL-RRL16HDF-24-1	ZIPLink high-density fused relay module, 16-point, sinking, SPDT socketed relays (included), LED indication, 24 VDC (coil), 5A @ 250 VAC, 5A @ 30 VDC, 35mm DIN rail mount. Fuses sold separately.	\$371
ZL-RRL16HDF-24-2	ZIPLink high-density fused relay module, 16-point, sourcing, SPDT socketed relays (included), LED indication, 24 VDC (coil), 5A @ 250 VAC, 5A @ 30 VDC, 35mm DIN rail mount. Fuses sold separately.	\$371
ZL-RRL16W-24-1	ZIPLink reduced-width relay module, 16-point, sinking, SPDT socketed relays (included), LED indication, 24 VDC (coil), 8A @ 250 VAC, 10A @ 30 VDC, 35mm DIN rail mount.	\$293
ZL-RRL16W-24-2	ZIPLink reduced-width relay module, 16-point, sourcing, SPDT socketed relays (included), LED indication, 24 VDC (coil), 8A @ 250 VAC, 10A @ 30 VDC, 35mm DIN rail mount.	\$293
ZL-RTB20	ZIPLink 20-pole feedthrough connector module, Mounts on 35 mm DIN rail part # DN-R35S1.	\$32
ZL-RTB20-1	ZIPLink reduced-width feedthrough module, 24-pole, 35mm DIN rail mount.	\$57
ZL-RTB40	ZIPLink 40-pole feedthrough connector module, Mounts on 35 mm DIN rail part # DN-R35S1.	\$52
ZL-RTB40-1	ZIPLink reduced-width feedthrough module, 48-pole, 35mm DIN rail mount.	\$100

ZL-RTB50	ZIPLink 50-pole feedthrough connector module, Mounts on 35 mm DIN rail part # DN-R35S1. For the SVA Servo Amps.	\$73
ZL-RTB-COM	ZIPLink common terminal module, 40-pole, 35mm DIN rail mount.	\$101
ZL-RTB-DB09	ZIPLink 9-pin male and female D-sub connectors to terminal blocks. Mounts on 35 mm DIN rail part # DN-R35S1.	\$34
ZL-RTB-DB15	ZIPLink 15-pin male and female D-sub connectors to terminal blocks. Mounts on 35 mm DIN rail part # DN-R35S1.	\$42
ZL-RTB-DB25	ZIPLink 25-pin male and female D-sub connectors to terminal blocks. Mounts on 35 mm DIN rail part # DN-R35S1.	\$54
ZL-RTB-RJ12	ZIPLink RJ12 connector to terminal blocks. Mounts on 35 mm DIN rail part # DN-R35S1.	\$29
ZL-TSD8-120	ZIPLink 8-channel transient voltage suppressor module, 120 VAC. Mounts on 35 mm DIN rail part # DN-R35S1.	\$43
ZL-TSD8-24	ZIPLink 8-channel transient voltage suppressor module, 24 VDC. Mounts on 35 mm DIN rail part # DN-R35S1.	\$62
Product Code	ZIPLinks Connector Cables - Click PLC	Aust\$
ZL-C0-CBL11	ZIPLink cable used to connect CLICK PLC I/O modules with 11 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$29
ZL-C0-CBL11-1	ZIPLink cable used to connect CLICK PLC I/O modules with 11 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$33
ZL-C0-CBL11-2	ZIPLink cable used to connect CLICK PLC I/O modules with 11 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meters (6.6 ft.) length	\$40
ZL-C0-CBL20	ZIPLink cable used to connect CLICK PLC I/O modules with 20 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$34
ZL-C0-CBL20-1	ZIPLink cable used to connect CLICK PLC I/O modules with 20 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$38
ZL-C0-CBL20-2	ZIPLink cable used to connect CLICK PLC I/O modules with 20 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meters (6.6 ft.) length	\$46
ZL-C0-CBL11-1P	ZIPLink PLC cable, allows Click PLC I/O modules with 11 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$28
ZL-C0-CBL11-2P	ZIPLink PLC cable, allows Click PLC I/O modules with 11 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$35
ZL-C0-CBL20-1P	ZIPLink PLC cable, allows Click PLC I/O modules with 20 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$33
ZL-C0-CBL20-2P	ZIPLink PLC cable, allows Click PLC I/O modules with 20 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$41
Product Code	ZIPLinks Connector Cables - DL05/06 PLC	Aust\$
ZL-D0-CBL8	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 8 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$27
ZL-D0-CBL8-1	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 8 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$31
ZL-D0-CBL8-2	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 8 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$39
ZL-D0-CBL10	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$28
ZL-D0-CBL10-2	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$40
ZL-D0-CBL13	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 13 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$30
ZL-D0-CBL13-1	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 13 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$34
ZL-D0-CBL13-2	ZIPLink cable used to connect DirectLOGIC 05/06 I/O modules with 13 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$42
ZL-D0-CBL24	ZIPLink cable used to connect DirectLOGIC 05/06 PLC output modules with a 24-pin connector to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$31
ZL-D0-CBL24-1	ZIPLink cable used to connect DirectLOGIC 05/06 PLC output modules with a 24-pin connector to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$34
ZL-D0-CBL24-2	ZIPLink cable used to connect DirectLOGIC 05/06 PLC output modules with a 24-pin connector to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$42
ZL-D0-CBL24-L	ZIPLink cable used to connect DirectLOGIC 05/06 PLC input modules with a 24-pin connector to a ZL-RTB20 or a ZL-LTB16-24 ZIPLink module, 24 AWG, 0.5 meter (1.6 ft.) length	\$31
ZL-D0-CBL24-1L	ZIPLink cable used to connect DirectLOGIC 05/06 PLC input modules with a 24-pin connector to a ZL-RTB20 or a ZL-LTB16-24 ZIPLink module, 24 AWG, 1.0 meter (3.3 ft.) length	\$34
ZL-D0-CBL24-2L	ZIPLink cable used to connect DirectLOGIC 05/06 PLC input modules with a 24-pin connector to a ZL-RTB20 or a ZL-LTB16-24 ZIPLink module, 24 AWG, 2.0 meter (6.6 ft.) length	\$42
ZL-D0-CBL24-1P	ZIPLink cable that allows DirectLOGIC 05/06 PLC I/O modules with a 24-pin connector to custom wire to third party devices, 24 AWG, 1.0 meter (3.3 ft.) length	\$24
ZL-D0-CBL24-2P	ZIPLink cable that allows DirectLOGIC 05/06 PLC I/O modules with a 24-pin connector to custom wire to third party devices, 24 AWG, 2.0 meter (6.6 ft.) length	\$32

ZL-D05-CBL18	ZIPLink PLC cable, allows DirectLOGIC 05 PLC fixed I/O with 18 terminals to connect to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input or output side terminal block of a DL05, 24AWG, 0.5 meter (1.6 ft.) length	\$50
ZL-D05-CBL18-1	ZIPLink PLC cable, allows DirectLOGIC 05 PLC fixed I/O with 18 terminals to connect to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input or output side terminal block of a DL05, 24AWG, 1.0 meter (3.3 ft.) length	\$54
ZL-D05-CBL18-2	ZIPLink PLC cable, allows DirectLOGIC 05 PLC fixed I/O with 18 terminals to connect to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input or output side terminal block of a DL05, 24AWG, 2.0 meter (6.6 ft.) length	\$61
ZL-D05-CBL22-1P	ZIPLink PLC cable, allows DirectLOGIC 05 PLC fixed I/O with 20 terminals to custom wire to 3rd party devices, can be used on the input or output side terminal block of a DL05, 24AWG, 1.0 meter (3.3 ft.) length	\$49
ZL-D05-CBL22-2P	ZIPLink PLC cable, allows DirectLOGIC 05 PLC fixed I/O with 20 terminals to custom wire to 3rd party devices, can be used on the input or output side terminal block of a DL05, 24AWG, 2.0 meter (6.6 ft.) length	\$60
ZL-D06X-CBL20	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed inputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input side terminal block only, 24AWG, 0.5 meter (1.6 ft.) length	\$56
ZL-D06X-CBL20-1	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed inputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input side terminal block only, 24AWG, 1.0 meter (3.3 ft.) length	\$60
ZL-D06X-CBL20-2	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed inputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the input side terminal block only, 24AWG, 2.0 meter (6.6 ft.) length	\$68
ZL-D06Y-CBL20	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed outputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the output side terminal block only, 24AWG, 0.5 meter (1.6 ft.) length	\$56
ZL-D06Y-CBL20-1	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed outputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the output side terminal block only, 24AWG, 1.0 meter (3.3 ft.) length	\$60
ZL-D06Y-CBL20-2	ZIPLink PLC cable, connects DirectLOGIC 06 PLC fixed outputs with 20 terminals to ZL-RTB20 ZIPLink module with a 24-pin connector, can be used on the output side terminal block only, 24AWG, 2.0 meter (6.6 ft.) length	\$68
ZL-D06-CBL24-1P	ZIPLink PLC cable, allows DirectLOGIC 06 PLC fixed I/O with 24 terminals to custom wire to 3rd party devices, can be used on the input or output side terminal block of a DL06, 24AWG, 1.0 meter (3.3 ft.) length	\$54
ZL-D06-CBL24-2P	ZIPLink PLC cable, allows DirectLOGIC 06 PLC fixed I/O with 24 terminals to custom wire to 3rd party devices, can be used on the input or output side terminal block of a DL06, 24AWG, 2.0 meter (6.6 ft.) length	\$65
ZL-D0-CBL8-1P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 8 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$28
ZL-D0-CBL8-2P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 8 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$35
ZL-D0-CBL10-1P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$29
ZL-D0-CBL10-2P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$36
ZL-D0-CBL13-1P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 13 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$29
ZL-D0-CBL13-2P	ZIPLink PLC cable, allows DirectLOGIC 05/06 PLC I/O modules with 13 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$37
Product Code	ZIPLinks Connector Cables - DL205	Aust\$
ZL-D2-CBL10	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$33
ZL-D2-CBL10-1	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$37
ZL-D2-CBL10-2	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 10 terminals to the ZL-RTB20 ZIPLink module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$45
ZL-D2-CBL19	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RR16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 24 AWG, 0.5 meter (1.6 ft.) length	\$57
ZL-D2-CBL19-1	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RR16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 24 AWG, 1.0 meter (3.3 ft.) length	\$61
ZL-D2-CBL19-2	ZIPLink cable used to connect DirectLOGIC 205 PLC I/O modules with 19 terminals to a ZL-RTB20, ZL-RFU20, ZL-RR16-24, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 24 AWG, 2.0 meter (6.6 ft.) length	\$69
ZL-D2-CBL19-1P	ZIPLink cable that allows DirectLOGIC 205 PLC I/O modules with 19 terminals to custom wire to third party devices, 24 AWG, 1.0 meter (3.3 ft.) length	\$52
ZL-D2-CBL19-2P	ZIPLink cable that allows DirectLOGIC 205 PLC I/O modules with 19 terminals to custom wire to third party devices, 24 AWG, 2.0 meter (6.6 ft.) length	\$61

ZL-D24-CBL40	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 0.5 meter (1.6 ft.) length	\$43
ZL-D24-CBL40-1	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$51
ZL-D24-CBL40-2	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 180-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$67
ZL-D24-CBL40-X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 0.5 meter (1.6 ft.) length	\$66
ZL-D24-CBL40-1X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$74
ZL-D24-CBL40-2X	ZIPLink cable used to connect any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with 40-pin connectors, 24 AWG, 45-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$90
ZL-D24-CBL40-1P	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 180-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$47
ZL-D24-CBL40-2P	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 180-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$62
ZL-D24-CBL40-1XP	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 45-degree cable exit on PLC connector, 1.0 meter (3.3 ft.) length	\$70
ZL-D24-CBL40-2XP	ZIPLink cable that allows any DirectLOGIC 205 PLC I/O modules or DirectLOGIC 405 PLC I/O modules with 40-pin connectors to custom wire to third party devices, 24 AWG, 45-degree cable exit on PLC connector, 2.0 meter (6.6 ft.) length	\$85
ZL-D24-CON-R	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Ribbon cable type connector, package of 2.	\$53
ZL-D24-CON-X	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Solder type connector, 45-degree exit, package of 2.	\$94
ZL-D24-CON	ZIPLink connector used with any DirectLOGIC 205 and DirectLOGIC 405 PLC I/O modules with 32 or 64 points for making custom cables. Solder type connector, 180-degree exit, package of 2.	\$48
ZL-D2-CBL10-1P	ZIPLink PLC cable, allows DirectLOGIC 205 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$33
ZL-D2-CBL10-2P	ZIPLink PLC cable, allows DirectLOGIC 205 PLC I/O modules with 10 terminals to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$40
Product Code	ZIPLinks Connector Cables - DL405	Aust\$
ZL-D4-CBL20	ZIPLink cable used to connect DirectLOGIC 405 PLC I/O modules with 20 terminals to a ZL-RTB20, ZL-RFU20, or ZL-LTB16-24 module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$55
ZL-D4-CBL20-1P	ZIPLink PLC cable, allows DirectLOGIC 405 PLC I/O modules with 20 terminals to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$53
Product Code	ZIPLinks Connector Cables - Misc	Aust\$
ZL-CBL24-1P	ZIPLink cable that allows any ZIPLink module with a 20-pin connector ready to custom wire to third party devices, 24 AWG, 1.0 meter (3.3 ft.) length	\$24
ZL-CBL24-2P	ZIPLink cable that allows any ZIPLink module with a 20-pin connector ready to custom wire to third party devices, 24 AWG, 2.0 meter (6.6 ft.) length	\$32
ZL-DB9-CBL-2	ZIPLink shielded cable with 9-pin D-sub male to female connectors, 28 AWG, 1.0 meter (3.3 ft.) length	\$11
ZL-DB9F-CBL-2P	ZIPLink pigtail cable with 9-pin D-sub female connector, 28AWG, 2 meter (6.6 ft.) length	\$11
ZL-DB15-CBL-2	ZIPLink shielded cable with 15-pin D-sub male to female connectors, 28 AWG, 2.0 meter (6.6 ft.) length	\$14
ZL-DB25-CBL-2	ZIPLink shielded cable with 25-pin D-sub male to female connectors, 28 AWG, 2.0 meter (6.6 ft.) length	\$16
ZL-RJ12-CBL-2	ZIPLink crossover cable with 6-pin RJ12 to 6-pin RJ12 connectors, 26 AWG, 2.0 meter (6.6 ft.) length	\$6
ZL-RJ12-CBL-2P	ZIPLink cable with 6-pin RJ12 connector to 6-wire pigtail, 26 AWG, 2.0 meter (6.6 ft.) length	\$5
ZL-CBL40-1P	ZIPLink cable, allows ZL-RTB40, ZL-RFU40 or ZL-LTB32-24 connector modules to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$37
ZL-CBL40-2P	ZIPLink cable, allows ZL-RTB40, ZL-RFU40 or ZL-LTB32-24 connector modules to custom wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$52
ZL-CBL50-1P	ZIPLink SureServo cable, allows SureServo amplifiers to custom wire to 3rd party devices, 28AWG, 1.0 meter (3.3 ft.) length	\$68
ZL-CBL50-2P	ZIPLink SureServo cable, allows SureServo amplifiers to custom wire to 3rd party devices, 28AWG, 2.0 meter (6.6 ft.) length	\$75
Product Code	ZIPLinks Connector Cables - Drives	Aust\$
GS-485HD15-CBL-2	ZIPLink GS Drives cable with 6-pin RJ12 connector to HD 15-pin male connector, 26 AWG, shielded, twisted pair, 2.0 meter (6.6 ft.) length. FOR ALL GS SERIES and DURAPULSE DRIVES	\$10

GS-485RJ12-CBL-2	ZIPLink GS series drive communication cable, 6-pin RJ12 connector to 6-pin RJ12 connector, 3-wire straight-through, 26AWG, 2.0 meter (6.6 ft.) length. Cable used in conjunction with ZL-CDM-RJ12xxx distribution module can access a compatible RS-485 device network.	\$10
GS-EDRV-CBL-2	ZIPLink GS series drive communication cable, 6-pin RJ12 connector to 6-pin RJ12 connector, 6-wire straight-through, 26AWG, 2.0 meter (6.6 ft.) length. Connects GS series and Durapulse series drives to the GS-EDRV Ethernet communication module.	\$10
GS-ISOCOCON-CBL-2	ZIPLink GS series drive communication cable, 6-pin RJ12 connector to FA-ISOCOCON 5-pin connector, 26AWG, 2.0 meter (6.6 ft.) length. Connects GS series and Durapulse series drives to FA-ISOCOCON universal serial communications converter.	\$13
GS-RJ12-CBL-2	ZIPLink GS Drives cable with 6-pin RJ12 connector to 6-pin RJ12 connector, 26 AWG, 2.0 meter (6.6 ft.) length. FOR THE GS2 SERIES DRIVES ONLY	\$10
SR44-485HD15-CBL-2	ZIPLink Stellar soft starter communication cable, 6-pin RJ45 connector to 15-pin high density connector, 3-wire, RS-485, 26AWG, 2.0 meter (6.6 ft.) length. Connects any Stellar SR44 series soft starter to a DL06 PLC, or a DL205 PLC with a D2-250-1 or D2-260 CPU.	\$15
SR44-485RJ45-CBL-2	ZIPLink Stellar soft starter communication cable, 6-pin RJ45 connector to 6-pin RJ12 connector, 3-wire, RS-485, 26AWG, 2.0 meter (6.6 ft.) length. Cable used in conjunction with ZL-CDM-RJ12xxx distribution module can access a compatible RS-485 device network.	\$12
STP-232HD15-CBL-2	ZIPLink SureStep drive communication cable, 6P4C RJ11 connector to 15-pin high density connector, 3-wire, RS-232, 26AWG, 2.0 meter (6.6 ft.) length. Connects STP-DRV-4850 or STP-DRV-80100 SureStep drives to a DL06 PLC, or a DL205 PLC with a D2-250-1 or D2-260 CPU.	\$15
STP-232RJ11-CBL	Spare 10 ft. RS-232 cable for programming and/or communicating to STP-DRV-80100 and STP-DRV-4850, female DB9 to modular (RJ11) 6P4C connector. (Note: Spare part item; one cable is already included with each 80100 and 4850 drive.)	\$22
STP-232RJ12-CBL-2	ZIPLink SureStep drive communication cable, 6P4C RJ11 connector to 6-pin RJ12 connector, 3-wire, RS-232, 26AWG, 2.0 meter (6.6 ft.) length. Connects STP-DRV-4850 or STP-DRV-80100 SureStep drives to a DL05 PLC, CLICK PLC or Productivity3000 PAC.	\$10
SVC-232RJ12-CBL-2	ZIPLink SureServo Drives cable with 6-pin RJ12 connector to a 6-pin IEEE connector, shielded, twisted pair, 2.0 meter (6.6 ft.) length. For all SureServo amplifiers.	\$11
SVC-485CFG-CBL-2	ZIPLink SureServo amplifier configuration cable, 6-pin IEEE 1394 connector to RJ45 connector, shielded, twisted pair, 2.0 meter (6.6 ft.) length. Cable in conjunction with USB-485M serial adapter connects any SureServo amplifier to a PC. Eliminates the need to reprogram networked servo drives from RS485 to RS232 when connecting to a PC.	\$16
SVC-485HD15-CBL-2	ZIPLink SureServo Drives cable with a HD 15-pin male to a 6-pin IEEE connector, shielded, twisted pair, 2.0 meter (6.6 ft.) length. For all Sure Servo amplifiers.	\$12
SVC-485RJ12-CBL-2	ZIPLink SureServo amplifier communication cable, RJ12 male to 6-pin IEEE connector, shielded, twisted pair, 2.0 meter (6.6 ft.) length. Cable used in conjunction with ZL-CDM-RJ12xxx distribution module can access a compatible RS-485 device network.	\$14
ZL-SVC-CBL50	ZIPLink SureServo cable used to connect any Sure Servo amplifier to a ZL-RTB50 ZIPLink module, shielded twisted pairs, 28 AWG, 0.5 meter (1.6 ft.) length. This cable is used with the SVA Servo amps and requires the ZL-RTB50.	\$76
ZL-SVC-CBL50-1	ZIPLink SureServo cable used to connect any Sure Servo amplifier to a ZL-RTB50 ZIPLink module, shielded twisted pairs, 28 AWG, 1.0 meter (3.3 ft.) length. This cable is used with the SVA Servo amps and requires the ZL-RTB50.	\$78
ZL-SVC-CBL50-2	ZIPLink SureServo cable used to connect any Sure Servo amplifier to a ZL-RTB50 ZIPLink module, shielded twisted pairs, 28 AWG, 2.0 meter (6.6 ft.) length. This cable is used with the SVA Servo amps and requires the ZL-RTB50.	\$83
Product Code	Ziplink Connectors - Productivity1000	Aust\$
ZL-P1-CBL10	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 90-degree connector angle, 1.6ft/0.5m cable length. For use with Productivity1000 I/O modules.	\$33
ZL-P1-CBL10-1	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 90-degree connector angle, 3.2ft/1m cable length. For use with Productivity1000 I/O modules.	\$39
ZL-P1-CBL10-1P	ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 90-degree connector angle, 3.2ft/1m cable length. For use with Productivity1000 I/O modules.	\$25
ZL-P1-CBL10-2	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 90-degree connector angle, 6.5ft/2m cable length. For use with Productivity1000 I/O modules.	\$37
ZL-P1-CBL10-2P	ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 90-degree connector angle, 6.5ft/2m cable length. For use with Productivity1000 I/O modules.	\$29
ZL-P1-CBL18	ZIPLink PLC I/O cable, 18-position terminal block to 24-pin connector, 90-degree connector angle, 1.6ft/0.5m cable length. For use with Productivity1000 I/O modules.	\$47
ZL-P1-CBL18-1	ZIPLink PLC I/O cable, 18-position terminal block to 24-pin connector, 90-degree connector angle, 3.2ft/1m cable length. For use with Productivity1000 I/O modules.	\$33
ZL-P1-CBL18-1P	ZIPLink PLC I/O cable, 18-position terminal block to pigtail, 90-degree connector angle, 3.2ft/1m cable length. For use with Productivity1000 I/O modules.	\$25
ZL-P1-CBL18-2	ZIPLink PLC I/O cable, 18-position terminal block to 24-pin connector, 90-degree connector angle, 6.5ft/2m cable length. For use with Productivity1000 I/O modules.	\$43
ZL-P1-CBL18-2P	ZIPLink PLC I/O cable, 18-position terminal block to pigtail, 90-degree connector angle, 6.5ft/2m cable length. For use with Productivity1000 I/O modules.	\$29

Product Code	Ziplink Connectors - Productivity2000	Aust\$
ZL-P2-CBL18	ZIPLink PLC I/O cable, for Productivity2000 modules, 18-position terminal block to 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$44
ZL-P2-CBL18-1	ZIPLink PLC I/O cable, for Productivity2000 modules, 18-position terminal block to 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$52
ZL-P2-CBL18-2	ZIPLink PLC I/O cable, for Productivity2000 modules, 18-position terminal block to 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$70
ZL-P2-CBL18-1P	ZIPLink PLC I/O cable, for Productivity2000 modules, 18-position terminal block to pigtail, 24 AWG, 1.0 meter (3.3 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$45
ZL-P2-CBL18-2P	ZIPLink PLC I/O cable, for Productivity2000 modules, 18-position terminal block to pigtail, 24 AWG, 2.0 meter (6.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$61
ZL-P2-CBL24	ZIPLink PLC I/O cable, for Productivity2000 modules, 24-pin connector to 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$56
ZL-P2-CBL24-1	ZIPLink PLC I/O cable, for Productivity2000 modules, 24-pin connector to 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$60
ZL-P2-CBL24-2	ZIPLink PLC I/O cable, for Productivity2000 modules, 24-pin connector to 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$56
ZL-P2-CBL24-1P	ZIPLink PLC I/O cable, for Productivity2000 modules, 24-pin connector to pigtail, 24 AWG, 1.0 meter (3.3 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$56
ZL-P2-CBL24-2P	ZIPLink PLC I/O cable, for Productivity2000 modules, 24-pin connector to pigtail, 24 AWG, 2.0 meter (6.6 ft.) length. See the ZIPLink selection guide for detailed usage and compatibility.	\$58
Product Code	Ziplink Connectors - Productivity3000	Aust\$
ZL-P3-CBL20	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08NAS, P3-08ND3S, P3-08TAS, P3-08TRS, P3-16TA, P3-16TD1, P3-TD1F, P3-16TD2, P3-16TD2F, P3-16TR, P3-08TRS-1) with 20-position terminal blocks to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$52
ZL-P3-CBL20-1	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08NAS, P3-08ND3S, P3-08TAS, P3-08TRS, P3-16TA, P3-16TD1, P3-TD1F, P3-16TD2, P3-16TD2F, P3-16TR, P3-08TRS-1) with 20-position terminal blocks to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$56
ZL-P3-CBL20-2	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08NAS, P3-08ND3S, P3-08TAS, P3-08TRS, P3-16TA, P3-16TD1, P3-TD1F, P3-16TD2, P3-16TD2F, P3-16TR, P3-08TRS-1) with 20-position terminal blocks to a ZL-RTB20, ZL-RFU20, or ZL-RRL16-24 module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$64
ZL-P3-CBL20-L	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08TD1S, P3-08TD2S, P3-16NA, P3-16ND3, P3-04ADS, P3-08AD, P3-16AD-1, P3-16AD-2, P3-04DA, P3-08DA-1, P3-08DA-2, P3-06DAS-1, P3-06DAS-2, P3-16DA-1, P3-16DA-2, P3-8AD4DA-1, or P3-8AD4DA-2) with 20-position terminal blocks to a ZL-RTB20 feedthrough module with a 24-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$52
ZL-P3-CBL20-1L	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08TD1S, P3-08TD2S, P3-16NA, P3-16ND3, P3-04ADS, P3-08AD, P3-16AD-1, P3-16AD-2, P3-04DA, P3-08DA-1, P3-08DA-2, P3-06DAS-1, P3-06DAS-2, P3-16DA-1, P3-16DA-2, P3-8AD4DA-1, or P3-8AD4DA-2) with 20-position terminal blocks to a ZL-RTB20 feedthrough module with a 24-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$56
ZL-P3-CBL20-2L	ZIPLink cable used to connect Productivity 3000 PAC I/O modules (P3-08TD1S, P3-08TD2S, P3-16NA, P3-16ND3, P3-04ADS, P3-08AD, P3-16AD-1, P3-16AD-2, P3-04DA, P3-08DA-1, P3-08DA-2, P3-06DAS-1, P3-06DAS-2, P3-16DA-1, P3-16DA-2, P3-8AD4DA-1, or P3-8AD4DA-2) with 20-position terminal blocks to a ZL-RTB20 feedthrough module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$64
ZL-P3-CBL20-P	ZIPLink cable that allows Productivity 3000 PAC I/O modules with 20-position terminal blocks to custom wire to 3rd party devices, 24 AWG, 0.5 meter (1.6 ft.) length	\$43
ZL-P3-CBL20-1P	ZIPLink cable that allows Productivity 3000 PAC I/O modules with 20-position terminal blocks to custom wire to 3rd party devices, 24 AWG, 1.0 meter (3.3 ft.) length	\$47
ZL-P3-CBL20-2P	ZIPLink cable that allows Productivity 3000 PAC I/O modules with 20-position terminal blocks to custom-wire to 3rd party devices, 24 AWG, 2.0 meter (6.6 ft.) length	\$56
ZL-CBL40	ZIPLink cable used to connect Productivity 3000 PAC I/O modules with 32 or 64-position terminal blocks to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with a 40-pin connector, 24 AWG, 0.5 meter (1.6 ft.) length	\$35
ZL-CBL40-S	Shielded ZIPLink PLC cable, connects Productivity3000 PAC High Speed I/O modules to the ZL-RTB40 (ZIPLink module with a 40-pin connector) 24 AWG, 0.5 meter (1.6 ft.) length.	\$43
ZL-CBL40-1S	Shielded ZIPLink PLC cable, connects Productivity3000 PAC High Speed I/O modules to the ZL-RTB40 (ZIPLink module with a 40-pin connector) 24 AWG, 1.0 meter (3.3 ft.) length.	\$53
ZL-CBL40-2S	Shielded ZIPLink PLC cable, connects Productivity3000 PAC High Speed I/O modules to the ZL-RTB40 (ZIPLink module with a 40-pin connector) 24 AWG, 2.0 meter (6.6 ft.) length.	\$72
ZL-CBL40-1	ZIPLink cable used to connect Productivity 3000 PAC I/O modules with 32 or 64-position terminal blocks to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with a 40-pin connector, 24 AWG, 1.0 meter (3.3 ft.) length	\$41

ZL-CBL40-2	ZIPLink cable used to connect Productivity 3000 PAC I/O modules with 32 or 64-position terminal blocks to a ZL-RTB40, ZL-RFU40, or ZL-LTB32-24 module with a 24-pin connector, 24 AWG, 2.0 meter (6.6 ft.) length	\$53
ZL-P3-CBL40-1P	ZIPLink PLC cable, allows Productivity3000 PAC I/O modules with 40-position terminal blocks to custom wire to 3rd party devices, 24AWG, 1.0 meter (3.3 ft.) length	\$37
ZL-P3-CBL40-2P	ZIPLink PLC cable, allows Productivity3000 PAC I/O modules with 40-position terminal blocks to custom-wire to 3rd party devices, 24AWG, 2.0 meter (6.6 ft.) length	\$51
Product Code	ZIPLinks Connector Cables - BRX PLC	Aust\$
ZL-BX-CBL15	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with 18-point and 36-point BRX PLCs.	\$40
ZL-BX-CBL15-1	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with 18-point and 36-point BRX PLCs.	\$47
ZL-BX-CBL15-2	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with 18-point and 36-point BRX PLCs.	\$64
ZL-BX-CBL15-1P	ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 3.2ft/1m cable length. For use with 18-point and 36-point BRX PLCs.	\$40
ZL-BX-CBL15-2P	ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 6.5ft/2m cable length. For use with 18-point and 36-point BRX PLCs.	\$60
ZL-BX-CBL20	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with 10-point BRX PLCs.	\$40
ZL-BX-CBL20-1	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with 10-point BRX PLCs.	\$47
ZL-BX-CBL20-2	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with 10-point BRX PLCs.	\$64
ZL-BX-CBL20-1P	ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 3.2ft/1m cable length. For use with 10-point BRX PLCs.	\$40
ZL-BX-CBL20-2P	ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 6.5ft/2m cable length. For use with 10-point BRX PLCs.	\$60
ZL-BX-CBL40-1S	ZIPLink PLC I/O cable, 40-pin connector to 40-pin connector, shielded, 3.2ft/1m cable length. For use with BRX series high-speed modules.	\$67
ZL-BXEM-CBL10	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with 8-point BRX expansion modules.	\$40
ZL-BXEM-CBL10-1	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with 8-point BRX expansion modules.	\$47
ZL-BXEM-CBL10-2	ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with 8-point BRX expansion modules.	\$64
ZL-BXEM-CBL10-1P	ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 3.2ft/1m cable length. For use with 8-point BRX expansion modules.	\$40
ZL-BXEM-CBL10-2P	ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 6.5ft/2m cable length. For use with 8-point BRX expansion modules.	\$60
ZL-BXEM-CBL15	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with 5-point and 12-point BRX expansion modules.	\$40
ZL-BXEM-CBL15-1	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with 5-point and 12-point BRX expansion modules.	\$47
ZL-BXEM-CBL15-2	ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with 5-point and 12-point BRX expansion modules.	\$64
ZL-BXEM-CBL15-1P	ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 3.2ft/1m cable length. For use with 5-point and 12-point BRX expansion modules.	\$40
ZL-BXEM-CBL15-2P	ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 6.5ft/2m cable length. For use with 5-point and 12-point BRX expansion modules.	\$60
ZL-BXEM-CBL20	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with 16-point BRX expansion modules.	\$40
ZL-BXEM-CBL20-1	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with 16-point BRX expansion modules.	\$47
ZL-BXEM-CBL20-2	ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with 16-point BRX expansion modules.	\$64
ZL-BXEM-CBL20-1P	ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 3.2ft/1m cable length. For use with 16-point BRX expansion modules.	\$40
ZL-BXEM-CBL20-2P	ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 6.5ft/2m cable length. For use with 16-point BRX expansion modules.	\$60
Product Code	3-Pole Pico (M8) Sensor Cables	Aust\$
CD08-0A-020-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 2 meter length, gray PVC outer jacket	\$24

CD08-0A-020-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 2 meter length, gray PVC outer jacket	\$24
CD08-0C-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 5 meter length, black PUR outer jacket	\$26
CD08-0C-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 5 meter length, black PUR outer jacket	\$26
CD08-0A-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 5 meter length, black PVC outer jacket	\$24
CD08-0A-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 5 meter length, black PVC outer jacket	\$24
CD08-0A-070-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 7 meter length, gray PVC outer jacket	\$38
CD08-0A-070-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 7 meter length, gray PVC outer jacket	\$38
CDP08-0A-010-AA	M8 patch cable with 8mm axial 3-pole female plug to 8mm axial 3-pole male plug, 1 meter length, gray PVC outer jacket	\$24
CDP08-0A-030-AA	M8 patch cable with 8mm axial 3-pole female plug to 8mm axial 3-pole male plug, 3 meter length, gray PVC outer jacket	\$29
CDP08-0A-010-BB	M8 patch cable with 8mm right angle 3-pole female plug to 8mm right angle 3-pole male plug, 1 meter length, gray PVC outer jacket	\$24
CDP08-0A-030-BB	M8 patch cable with 8mm right angle 3-pole female plug to 8mm right angle 3-pole male plug, 3 meter length, gray PVC outer jacket	\$24
Product Code	4-Pole Pico (M8) Sensor Cables	Aust\$
CD08-0G-020-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 2 meter length, black PVC outer jacket Use with DFP/DFT models.	\$20
CD08-0G-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 5 meter length, black PVC outer jacket Use with DFP/DFT models.	\$24
CD08-0G-100-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 10 meter length, black PVC outer jacket Use with DFP/DFT models.	\$30
CD08-0W-020-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 2 meter length, black PVC outer jacket Use with DFP/DFT models.	\$20
CD08-0W-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 5 meter length, black PVC outer jacket Use with DFP/DFT models.	\$24
CD08-0W-100-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 10 meter length, black PVC outer jacket Use with DFP/DFT models.	\$30
Product Code	3-Pole Micro (M12) Sensor Cables	Aust\$
CD12M-0B-050-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 3-pole, 5 meter length, black PVC outer jacket. Do not use with SU and TU series sensors.	\$24
CD12M-0D-050-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 3-pole, 5 meter length, black PUR outer jacket. Do not use with SU and TU series sensors.	\$29
CD12M-0D-050-C1	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 3-pole, 5 meter length, black PUR outer jacket. Do not use with SU and TU series sensors.	\$29
Product Code	4-Pole Micro (M12) Sensor Cables	Aust\$
CD12L-0B-020-A0	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 2 meter length, gray PVC outer jacket	\$24
CD12L-0B-020-C0	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 2 meter length, gray PVC outer jacket	\$24
CD12M-0B-070-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 7 meter length, gray PVC outer jacket	\$38
CD12M-0B-070-C1	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 7 meter length, gray PVC outer jacket	\$38
7000-12221-2141000	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 10 meter (32.8 feet) length, gray PVC outer jacket	\$44
7000-12341-2141000	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 10 meter (32.8 feet) length, gray PVC outer jacket	\$44
7000-12221-2141500	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 15 meter (49.2 feet) length, gray PVC outer jacket	\$59
7000-12341-2141500	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 15 meter (49.2 feet) length, gray PVC outer jacket	\$59
EVC178	M12 cable for quick-disconnect sensors, 12mm right angle female plug, 4-pole, 10-36 VDC PNP LED indication, 2 meter length, black PUR outer jacket	\$32
EVC179	M12 cable for quick-disconnect sensors, 12mm right angle female plug, 4-pole, 10-36 VDC PNP LED indication, 5 meter length, black PUR outer jacket	\$34
EVC180	M12 cable for quick-disconnect sensors, 12mm right angle female plug, 4-pole, 10-36 VDC PNP LED indication, 10 meter length, black PUR outer jacket	\$41
CDP12-0B-010-AA	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, 1 meter length, gray PVC jacket	\$24
CDP12-0B-030-AA	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, 3 meter length, gray PVC jacket	\$24

CDP12-0B-010-BB	M12 patch cable, 12mm right angle 4-pole female plug to 12mm right angle 4-pole male plug, 1 meter length, gray PVC jacket	\$24
CDP12-0B-030-BB	M12 patch cable, 12mm right angle 4-pole female plug to 12mm right angle 4-pole male plug, 3 meter length, gray PVC jacket	\$29
EVC322	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 0.3 meter length, black PUR outer jacket	\$32
EVC323	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 0.6 meter length, black PUR outer jacket	\$35
EVC324	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 1 meter length, black PUR outer jacket	\$37
EVC325	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 2 meter length, black PUR outer jacket	\$43
EVC326	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 5 meter length, black PUR outer jacket	\$50
EVC327	M12 patch cable, 12mm right angle 4-pole female plug with 10-36 VDC PNP LED indication to 12mm axial 4-pole male plug, 10 meter length, black PUR outer jacket	\$63
Product Code	5-Pole Micro (M12) Sensor Cables	Aust\$
7000-12241-2151000	M12 cable for quick-disconnect sensors, 12mm axial female, 5-pole, gray PVC outer jacket, 10 meter (32.8 ft) length, IP67 rated.	\$53
7000-12241-2150300	M12 cable for quick-disconnect sensors, 12mm axial female, 5-pole, gray PVC outer jacket, 3 meter (9.84 ft) length, IP67 rated.	\$28
7000-12361-2150300	M12 cable for quick-disconnect sensors, 12mm right-angle female, 5-pole, gray PVC outer jacket, 3 meter (9.84 ft) length, IP67 rated.	\$28
7000-12361-2151000	M12 cable for quick-disconnect sensors, 12mm right-angle female, 5-pole, gray PUR outer jacket, 10 meter (32.8 ft) length, IP67 rated.	\$53
7000-12241-2150500	M12 cable for quick-disconnect sensors, 12mm axial female, 5-pole, gray PVC outer jacket, 5 meter (16.48 ft) length, IP67 rated.	\$35
7000-12361-2150500	M12 cable for quick-disconnect sensors, 12mm right-angle female, 5-pole, gray PVC outer jacket, 5 meter (16.48 ft) length, IP67 rated.	\$35
Product Code	Field Wireable Connectors	Aust\$
7000-08341-0000000	Field wireable connector, M8, axial, male, 4-pole, 20 to 24 AWG (0.5 to 0.25 mm sq.), insulation displacement connection (IDC), 4 to 5.1 mm diameter cable exit, IP67	\$26
7000-08331-0000000	Field wireable connector, M8, axial, male, 3-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.5 to 5.1 mm diameter cable exit, IP67	\$27
7000-08351-0000000	Field wireable connector, M8, axial, male, 4-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.5 to 5.1 mm diameter cable exit, IP67	\$29
7000-08371-0000000	Field wireable connector, M8, axial, female, 3-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.5 to 5.1 mm diameter cable exit, IP67	\$28
7000-08391-0000000	Field wireable connector, M8, axial, female, 4-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.5 to 5.1 mm diameter cable exit, IP67	\$29
7000-12481-0000000	Field wireable connector, M12, axial, male, 4-pole, 20 to 24 AWG (0.5 to 0.25 mm sq.), insulation displacement connection (IDC), 4 to 5.1 mm diameter cable exit, IP67	\$23
7000-12601-0000000	Field wireable connector, M12, axial, female, 4-pole, 20 to 24 AWG (0.5 to 0.25 mm sq.), insulation displacement connection (IDC), 4 to 5.1 mm diameter cable exit, IP67	\$26
7000-12491-0000000	Field wireable connector, M12, axial, male, 4-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.9 to 5.1 mm diameter cable exit, IP67	\$26
7000-12611-0000000	Field wireable connector, M12, axial, female, 4-pole, 22 to 26 AWG (0.34 to 0.14 mm sq.), insulation displacement connection (IDC), 2.9 to 5.1 mm diameter cable exit, IP67	\$29
7000-12561-0000000	Field wireable connector, M12, right-angle, male, 4-pole, 20 to 24 AWG (0.5 to 0.25 mm sq.), insulation displacement connection (IDC), 4 to 5.1 mm diameter cable exit, IP67	\$32
7000-12681-0000000	Field wireable connector, M12, right-angle, female, 4-pole, 20 to 24 AWG (0.5 to 0.25 mm sq.), insulation displacement connection (IDC), 4 to 5.1 mm diameter cable exit, IP67	\$35
7000-12701-0000000	Field wireable connector, M12, axial, male, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$21
7000-12721-0000000	Field wireable connector, M12, axial, male, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$26
7000-12901-0000000	Field wireable connector, M12, axial, female, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$21
7000-12921-0000000	Field wireable connector, M12, axial, female, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$26
7000-12741-0000000	Field wireable connector, M12, axial, male, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$21

7000-12761-0000000	Field wireable connector, M12, axial, male, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$26
7000-12941-0000000	Field wireable connector, M12, axial, female, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$21
7000-12961-0000000	Field wireable connector, M12, axial, female, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$26
7000-12821-0000000	Field wireable connector, M12, right-angle, male, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$21
7000-12981-0000000	Field wireable connector, M12, right-angle, female, 4-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 4 to 6 mm diameter cable exit, IP67	\$21
7000-41121-0000000	T-coupler, two-branch molded junction splitter, one M12 male 5-pole trunk, two M12 female 4-pole branches, standard distribution function (normally open)	\$38
7000-41141-0000000	T-coupler, two-branch molded junction splitter, one M12 male 5-pole trunk, two M12 female 5-pole branches, parallel switch mode function	\$38
7000-41181-0000000	T-coupler, two-branch molded junction splitter, one M12 male 5-pole trunk, two M12 female 5-pole branches, standard distribution function (normally open or normally closed)	\$38
7000-41201-0000000	T-coupler, two-branch molded junction splitter, one M12 male 4-pole trunk, two M8 female 3-pole branches, standard distribution function (normally open)	\$38
7000-17301-0000000	Field wireable connector, M12, axial, male, 8-pole, 20AWG (0.5 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$59
7000-17311-0000000	Field wireable connector, M12, right-angle, male, 8-pole, 20AWG (0.5 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$59
7000-17321-0000000	Field wireable connector, M12, axial, female, 8-pole, 20AWG (0.5 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$59
7000-17331-0000000	Field wireable connector, M12, right-angle, female, 8-pole, 20AWG (0.5 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$59
7000-13321-0000000	Field wireable connector, shielded, M12, axial, male, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$53
7000-13361-0000000	Field wireable connector, shielded, M12, right-angle, male, 5-pole, 18AWG (0.75 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$70
7000-17341-0000000	Field wireable connector, shielded, M12, axial, male, 8-pole, 20AWG (0.5 mm sq.) maximum, screw terminal connection, 6 to 8 mm diameter cable exit, IP67	\$70
Product Code	Micro (M12) Receptacles	Aust\$
7231-13501-9710050	M12 receptacle, front mount, male, 4-pole, 22AWG (0.34 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$22
7231-13501-9710100	M12 receptacle, front mount, male, 4-pole, 22AWG (0.34 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$25
7231-13541-9710050	M12 receptacle, front mount, female, 4-pole, 22AWG (0.34 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$22
7231-13541-9710100	M12 receptacle, front mount, female, 4-pole, 22AWG (0.34 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$25
7231-13521-9720050	M12 receptacle, front mount, male, 5-pole, 22AWG (0.34 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$25
7231-13521-9720100	M12 receptacle, front mount, male, 5-pole, 22AWG (0.34 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$28
7231-13561-9720050	M12 receptacle, front mount, female, 5-pole, 22AWG (0.34 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$25
7231-13561-9720100	M12 receptacle, front mount, female, 5-pole, 22AWG (0.34 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$28
7231-17161-9730050	M12 receptacle, front mount, male, 8-pole, 24AWG (0.25 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$38
7231-17161-9730100	M12 receptacle, front mount, male, 8-pole, 24AWG (0.25 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$41
7231-17181-9730050	M12 receptacle, front mount, female, 8-pole, 24AWG (0.25 mm sq.), 0.5-meter (1.6-feet) polypropylene insulated wires. Mounting nut included.	\$38
7231-17181-9730100	M12 receptacle, front mount, female, 8-pole, 24AWG (0.25 mm sq.), 1-meter (3.3-feet) polypropylene insulated wires. Mounting nut included.	\$41
7000-42111-0000000	M12 bulkhead receptacle, male / female, 5-pole. Mounting nut included.	\$44
7000-48111-0000000	M12 bulkhead receptacle, male / female, 8-pole. Mounting nut included.	\$59
Product Code	4-Pole Micro (M12) Shielded Sensor Cables	Aust\$

7000-13201-3310500	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$56
7000-13261-3310500	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$56
7000-13201-3311000	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$85
7000-13261-3311000	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$85
Product Code	5-Pole Micro (M12) Shielded Sensor Cables	Aust\$
7000-13221-3490500	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 5-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$65
7000-13281-3490500	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 5-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$65
7000-13221-3491000	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 5-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$100
7000-13281-3491000	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 5-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$100
Product Code	8-Pole Micro (M12) Shielded Sensor Cables	Aust\$
7000-17121-2940500	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 8-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$106
7000-17141-2940500	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 8-pole, 5 meter (16.4 feet) length, gray PUR outer jacket	\$106
7000-17121-2941000	M12 shielded cable for quick-disconnect sensors, 12mm axial female plug, 8-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$161
7000-17141-2941000	M12 shielded cable for quick-disconnect sensors, 12mm right-angle female plug, 8-pole, 10 meter (32.8 feet) length, gray PUR outer jacket	\$161
Product Code	Micro (M12) Harsh Duty Sensor Cables	Aust\$
EVT221	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 5 meter length, orange PVC outer jacket suitable for food and beverage applications	\$37
EVT222	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 5 meter length, orange PVC outer jacket suitable for food and beverage applications	\$37
EVT223	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 10 meter length, orange PVC outer jacket suitable for food and beverage applications	\$51
EVT224	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 10 meter length, orange PVC outer jacket suitable for food and beverage applications	\$51
EVT225	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 0.3 meter length, orange PVC outer jacket suitable for food and beverage applications	\$45
EVT226	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 0.3 meter length, orange PVC outer jacket suitable for food and beverage applications	\$48
EVT227	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 0.6 meter length, orange PVC outer jacket suitable for food and beverage applications	\$50
EVT228	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 0.6 meter length, orange PVC outer jacket suitable for food and beverage applications	\$54
EVT229	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 1 meter length, orange PVC outer jacket suitable for food and beverage applications	\$62
EVT230	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 1 meter length, orange PVC outer jacket suitable for food and beverage applications	\$45
EVT231	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 2 meter length, orange PVC outer jacket suitable for food and beverage applications	\$48
EVT232	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 2 meter length, orange PVC outer jacket suitable for food and beverage applications	\$50
EVT233	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 5 meter length, orange PVC outer jacket suitable for food and beverage applications	\$54
EVT234	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection, 5 meter length, orange PVC outer jacket suitable for food and beverage applications	\$62
E18446	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 5 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$63

E18447	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 5 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$78
E18448	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 10 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$63
E18449	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 10 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$78
Product Code	Programming Cables	Aust\$
D2-DSCBL	12 ft. (3.66m) RS-232 shielded PC programming cable for DirectLOGIC DL05, DL06, DL105, DL205, D3-350 and D4-450 CPUs, Do-more H2 series CPUs, and CLICK CPUs. 9-pin D-shell female connector to an RJ12 6P6C connector.	\$32
D2-DSCBL-1	12 ft. (3.66m) RS-232 shielded PC programming cable for DL06, D2-250(-1), D2-260 CPUs and D0-DCM. 9-pin D-shell female connector to a 15-pin male HD15 connector.	\$51
D2-DSCBL-2	12 ft. (3.66m) shielded pigtail cable for port 2 of a DL06, D2-250(-1) or D2-260 CPU. 15-pin D-shell male SVGA connector to 14 tinned wires.	\$62
D3-DSCBL-2	12 ft. (3.66m) RS-232 shielded PC programming cable for the D3-330 and D3-330P CPUs. An RS232 Data Communications Unit is also required to use this cable. 9-pin D-shell female connector to a 25-pin D-shell male connector. Can also be used to connect to the bottom port of a DL405 or D3-350 CPU, or to DL205/DL305/DL405 DCM modules.	\$52
D4-DSCBL	12 ft. (3.66m) RS-232 shielded PC programming cable for the 15-pin port on the DL405 CPUs. 9-pin D-shell female connector to a 15-pin D-shell male connector. For programming over the DL405 25-pin port, use D3-DSCBL-2.	\$52
DA-DSCBL	Single kit containing 1 each of: D2-DSCBL, D3-DSCBL-1, D3-DSCBL-2, D4-DSCBL. Saves over the price of cables purchased separately.	\$219
EA-MG-PGM-CBL	6 ft. PC programming cable assembly for C-more micro EA1 series STN panels, CLICK CPUs, DoMore H2 series CPUs, and DirectLogic CPUs with RJ12 programming ports. Assembly includes (1) standard USB A-type connector to B-type connector cable, (1) custom converter, and (1) RS-232C cable with RJ12 modular connector on each end (also sold separately as DV-1000CBL.) (Note: This cable assembly uses the PC's USB port and converts the signals to serial transmissions. The USB port supplies 5 VDC to the Micro-Graphic panel for configuration operations).	\$109
USB-RS232	6 ft. USB to RS-232C serial adapter cable transparently connects serial devices to PC applications via a USB port. USB-A male connector to 9-pin D-shell male connector. If needed, drivers can be downloaded from http://support.automationdirect.com/products/usbrs232.html (choose USB-RS232 adapter driver).	\$75
USB-CBL-AB3	3 ft. (0.9 meter) standard USB cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$19
USB-CBL-AB6	6 ft. (1.8 meter) standard USB cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$20
USB-CBL-AB10	10 ft. (3 meter) standard USB cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$39
USB-CBL-AB15	15 ft. (4.6 meter) standard USB cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$49