

	HMI - Operator Panels	
	C-more EA9 Operator Panels	
Product Code	C-more EA9 Operator Panels	Aust\$
EA9-T6CL-R	C-more EA9 series touch screen interface panel, 6-inch color TFT (5.7 inch viewable screen), base model, 64k colors, 320 x 240 pixel QVGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (1) serial port, USB 2.0 Type A and B ports, supports SD memory card, no Ethernet support. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 189.5mm x 140mm	\$990
EA9-T6CL	C-more EA9 series touch screen interface panel, 6-inch color TFT (5.7 inch viewable screen), 64k colors, 320 x 240 pixel QVGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (3) serial ports, USB 2.0 Type A and B ports and Ethernet port; supports SD memory card. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 189.5mm x 140mm	\$1,419
EA9-T7CL-R	C-more EA9 series touch screen HMI, 7in color TFT LCD, widescreen, 800 x 480, WVGA, supports (1) serial, (1) Ethernet and (2) USB ports and (1) memory card slot. Cutout = 189.5mm x 140mm	\$1,039
EA9-T7CL	C-more EA9 series touch screen HMI, 7in color TFT LCD, widescreen, 800 x 480, WVGA, supports (3) serial, (1) Ethernet and (2) USB ports, (1) memory card slot and (1) audio line out. Cutout = 189.5mm x 140mm	\$1,210
EA9-T8CL	C-more EA9 series touch screen interface panel, 8-inch color TFT (8.4 inch viewable screen), 64k colors, 800 x 600 pixel SVGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (3) serial ports, USB 2.0 Type A and B ports and Ethernet port; supports SD memory card. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 235mm x 179.6mm	\$1,995
EA9-T10CL	C-more EA9 series touch screen interface panel, 10-inch color TFT (10.4 inch viewable screen), 64k colors, 800 x 600 pixel SVGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (3) serial ports, USB 2.0 Type A and B ports and Ethernet port; supports SD memory card. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 302.3mm x 226.3mm	\$2,638
EA9-T10WCL	C-more EA9 series touch screen HMI, 10in color TFT LCD, widescreen, 1024 x 600 pixel, WSVGA, LED backlight, supports (3) serial, (1) Ethernet and (2) USB ports, (1) memory card slot and (1) audio line out. Cutout = 235mm x 179.6mm	\$1,428
EA9-T12CL	C-more EA9 series touch screen interface panel, 12-inch color TFT (12.1 inch viewable screen), 64k colors, 800 x 600 pixel SVGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (3) serial ports, USB 2.0 Type A and B ports and Ethernet port; supports (2) SD memory cards. Includes HDMI video out. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 319.3mm x 259.6mm	\$3,635
EA9-T15CL	C-more EA9 series touch screen interface panel, 15-inch color TFT (15 inch viewable screen), 64k colors, 1024 x 768 pixel XGA screen resolution, 800 MHz CPU, 12-24 VDC powered, NEMA 4/4X, IP65 (when mounted correctly; for indoor use only), non-replaceable LED backlight. Includes (3) serial ports, USB 2.0 Type A and B ports and Ethernet port; supports (2) SD memory cards. Includes HDMI video out. Compatible with EA9-PGMSW programming software version 5.0 or later. Cutout = 381.3mm x 286.3mm	\$3,990
EA9-T15CL-R	C-more EA9 series touch screen HMI, 15in color TFT LCD, 1024 x 768 pixel, XGA, LED backlight, supports (1) serial, (1) Ethernet and (2) USB ports and (2) memory card slots. Cutout = 381.3mm x 286.3mm	\$2,750
EA9-USER-M	C-more touch panel user manual, contains hardware specifications and programming information for C-more EA9 series touch panels.	Free Download
Product Code	C-more Headless HMI	Aust\$
EA9-RHMI	C-more EA9 series headless HMI, supports (2) serial, (1) Ethernet, (2) USB ports and (1) HDMI audio/video out and (1) memory card slot.	\$949
EA9-RHMI-USER-M	User manual, download only . For use with C-more EA9 series headless HMI.	Free Download
Product Code	C-more EA9 Software	Aust\$
EA9-PGMSW	C-more Windows programming software, available for free download .	Free Download
Product Code	C-more EA9 Cables & Accessories	Aust\$

EA-2CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a BRX*, Click, DL05, DL06, DL105, DL205, D3-350 or D4-450 CPU or Productivity3000 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ12 modular connector (* BX-P-SER2-RJ12 is required).	\$41
EA-2CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL06, D2-250(-1) or D2-260 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin male HD connector.	\$41
EA-3CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D3-340 CPU top or bottom port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to RJ11 modular connector.	\$41
EA-4CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a DL405 (top port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$41
EA-4CBL-2	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a D2-DCM, D3-350 (bottom port), a D3-232-DCU installed on a D3-330 or D3-340, or DL405 (bottom port) CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$41
EA-90-30-CBL	Shielded cable to connect any C-more touch panel to a GE Fanuc Series 90/30 or 90/70 serial port using SNPX protocol. 3m (9.8 ft) RS422A cable, 15-pin D-shell male connector to 15-pin D-shell male connector.	\$41
EA-SLC-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC 5/03, 5/04 or 5/05 CPU with DF-1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 9-pin D-shell female connector.	\$41
EA-PLC5-232-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B PLC5 CPU with a DF1 port. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$41
EA-MITSU-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$41
EA-MITSU-CBL-1	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to a Mitsubishi FX Series CPU. 3m (9.8 ft) RS422C cable, 15-pin D-shell male connector to 8-pin mini DIN connector.	\$41
EA-OMRON-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an Omron C200 or C500 CPU with HostLink protocol. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 25-pin D-shell male connector.	\$41
EA-DH485-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B SLC500 CPU with a DH485 port, 3m (9.8 ft) cable	\$41
EA-MLOGIX-CBL	Shielded cable to connect any C-more touch panel or C-more micro-graphic panel to an A-B Micrologix 1000, 1200 or 1500 CPU. 3m (9.8 ft) RS232C cable, 15-pin D-shell male connector to 8-pin DIN connector.	\$79
USB-CBL-AB3	3-ft. (0.9 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$19
USB-CBL-AB6	6-ft. (1.8 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$20
USB-CBL-AB10	10-ft. (3 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$39
USB-CBL-AB15	15-ft. (4.6 meter) standard USB 2.0 cable with Standard-A plug to Standard-B plug, suitable for all USB devices	\$49
EA-SD-CARD	SD memory card for non-volatile storage, 2GB industrial grade. 85 degrees C maximum operating temperature makes it suitable for data logging in industrial applications. Recommended for the C-more EA9 series touch panels.	\$213
EA9-6-GSK	Panel mounting gasket, replacement, for C-more EA9-T6CL(-R) 6-inch touch panels, NEMA 4/4X	\$35
EA9-8-GSK	Panel mounting gasket, replacement, for C-more EA9-T8CL 8-inch touch panel, NEMA 4/4X	\$40
EA9-10-GSK	Panel mounting gasket, replacement, for C-more EA9-T10CL 10-inch touch panel, NEMA 4/4X	\$46
EA9-10W-GSK	Panel mounting gasket, replacement. For use with C-more EA9-T10WCL 10in HMI.	\$44
EA9-12-GSK	Panel mounting gasket, replacement, for C-more EA9-T12CL 12-inch touch panel, NEMA 4/4X	\$50
EA9-15-GSK	Panel mounting gasket, replacement, for C-more EA9-T15CL 15-inch touch panel, NEMA 4/4X	\$61
EA9-BRK	Panel mounting brackets, replacement, for C-more EA9 series touch panels. Package of 8 brackets and screws.	\$65
EA9-LBL	Blank label insert for front bezel, replacement, for C-more EA9 series touch panels. Package of 10.	\$54
EA9-3TB	3-pole terminal block, replacement, for 3-wire RS485 communications port on C-more EA9 series panels. Package of 2.	\$22
EA-AC	AC/DC Adapter for C-more EA7 and EA9 series touch panels; powered from a 100-240 VAC, 50/60 Hertz power source. Provides 24VDC at 1.5A. Power Fault features help protect data being logged to Compact Flash or SD card during power failures. C-more EA7 series panels must have firmware version 1.21 Build 6.18E or higher for proper operation	\$159
EA-6-COV2	Non-glare protective overlay, 6-inch, protects C-more touch screen and helps reduce glare from external light sources. Compatible with C-more EA7 and EA9 series and C-more Micro-Graphic 6-inch panels. Package of 3.	\$79

EA-7-COV2	Screen protector, non-glare, 7in. Package of 3. For use with C-more 7in panels.	\$81
EA-8-COV2	Non-glare protective overlay, 8-inch, protects C-more touch screen and helps reduce glare from external light sources. Compatible with C-more EA7, EA9 and EA3 series 8-inch panels. Package of 3.	\$85
EA-10-COV2	Non-glare protective overlay, 10-inch, protects C-more touch screen and helps reduce glare from external light sources. Compatible with C-more EA7, EA9 and EA3 series 10-inch panels. Package of 3.	\$97
EA-10W-COV2	Screen protector, non-glare, 10in. Package of 3. For use with C-more EA9-T10WCL widescreen HMI.	\$98
EA-12-COV2	Non-glare protective overlay, 12-inch, protects C-more touch screen and helps reduce glare from external light sources. Compatible with C-more EA7 and EA9 series 12-inch panels. Package of 3.	\$99
EA-15-COV2	Non-glare protective overlay, 15-inch, protects C-more touch screen and helps reduce glare from external light sources. Compatible with C-more EA7 and EA9 series 15-inch panels. Package of 3.	\$117