

	Motor Controls	
	Power Supplies	
Product Code	RHINO Power Supplies	Aust\$
PSB12-015-P	RHINO switching power supply, 12 VDC (adjustable), 1.25A (15W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$47
PSB12-030-P	RHINO switching power supply, 12 VDC (adjustable), 2.5A (30W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$52
PSB12-060	RHINO switching power supply, 12 VDC (adjustable), 5A (60W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$82
PSB12-100	RHINO switching power supply, 12 VDC (adjustable), 8.3A (100W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$123
PSB24-060	RHINO switching power supply, 24 VDC (adjustable), 2.5A (60W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$80
PSB24-060-P	RHINO switching power supply, 24 VDC (adjustable), 2.5A (60W) output, 85-264 VAC / 120-375 VDC universal input, plastic case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$62
PSB24-060S-P	RHINO switching power supply, 24VDC, 2.5A (60W) output, 85-264 VAC input, overvoltage and overload protection, plastic case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, UL 1310 recognized for NEC Class 2 compliance, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$78
PSB24-060S	RHINO switching power supply, 24VDC, 2.5A (60W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 removable screw terminal plugs, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$93
PSB24-060S-3	RHINO switching power supply, 24VDC, 2.5A (60W) output, 320-600 VAC 3-phase universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, CE marked.	\$129
PSB24-120	RHINO switching power supply, 24 VDC (adjustable), 5A (120W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$138
PSB24-120S	RHINO switching power supply, 24VDC, 5A (120W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 removable screw terminal plugs, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$166
PSB24-120S-3	RHINO switching power supply, 24VDC, 5A (120W) output, 320-600 VAC 3-phase universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, CE marked.	\$169
PSB24-240	RHINO switching power supply, 24 VDC (adjustable), 10A (240W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$249
PSB24-240S	RHINO switching power supply, 24VDC, 10A (240W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 removable screw terminal plugs, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$269
PSB24-240S-3	RHINO switching power supply, 24VDC, 10A (240W) output, 320-600 VAC 3-phase universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, CE marked.	\$274
PSB24-480	RHINO switching power supply, 24 VDC (adjustable), 20A (480W) output, 85-264 VAC / 120-375 VDC universal input, aluminum case with built-in 35mm DIN rail mounting adapter, screw terminals, status indication LED. UL508 listed, UL60950-1 recognized, CSA certified, CE marked.	\$377
PSB24-480S	RHINO switching power supply, 24VDC, 20A (480W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$419
PSB24-480S-3	RHINO switching power supply, 24VDC, 20A (480W) output, 320-600 VAC 3-phase universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, CE marked.	\$388
PSB24-960S-3	RHINO switching power supply, 24VDC, 40A (960W) output, 320-600 VAC 3-phase universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, CE marked.	\$583
PSB24-BFM20S	RHINO buffer module for use with RHINO PSB24 power supplies, 22.8-28.8 VDC input, 22-28 VDC (adjustable) output is dependent on input voltage, 20A maximum current, overvoltage and overload protection, selection switch for voltage level to start buffering, Inhibit input for remote shut down, output signals for remote stand-by mode and buffering mode indication, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$332
PSB48-120S	RHINO switching power supply, 48VDC (adjustable), 2.5A (120W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 removable screw terminal plugs, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$169
PSB48-240S	RHINO switching power supply, 48VDC (adjustable), 5A (240W) output, 85-264 VAC / 120-375 VDC universal input, overvoltage and overload protection, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 removable screw terminal plugs, status indication LED. UL 508 listed, UL 60950-1 recognized, CSA certified, approved for Class I, Division 2 hazardous locations, CE marked.	\$283
PSB48-480S	RHINO switching power supply, 48 VDC (adjustable) output, 10A, 480W, 85-264 VAC / 120-375 VDC input, 1-phase, aluminum housing, 35mm DIN rail mount, screw terminals, hazardous location rated.	\$378
PSB60-REM20S	RHINO redundancy module for use with RHINO PSB24 or PSB48 power supplies, two 22-60 VDC inputs, 20A maximum current, input voltage alarm relay and LED indication, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks. UL 508 recognized, UL 60950-1 recognized, approved for Class I, Division 2 hazardous locations, CE marked.	\$82

PSB60-REM40S	RHINO redundancy module for use with RHINO PSB24 or PSB48 power supplies, two 22-60 VDC inputs, 40A maximum current, input voltage alarm relay and LED indication, aluminum case with built-in 35mm DIN rail mounting adapter, IP20 screw terminal blocks. UL 508 recognized, UL 60950-1 recognized, approved for Class I, Division 2 hazardous locations, CE marked.	\$97
PSB-CVR	Replacement terminal covers for all RHINO PSB series power supplies	\$12
PSS0524-100	RHINO dual output switching power supply, 24VDC (adjustable) 2.7A (65W) output, 5VDC (fixed) 7A (35W) output, 85-264 VAC / 125-375 VDC universal input, overvoltage and overload protection, enclosed panel mount, aluminum case with mounting holes for mounting in two planes, barrier screw terminal blocks, status indication LED. UL 60950-1 recognized, CE marked.	\$95
PSS12-035	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 2.9A (35W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$45
PSS12-050	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 4.1A (50W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$45
PSS12-100	RHINO enclosed panel mount switching power supply, 12 VDC (adjustable), 8.3A (100W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$69
PSS24-035	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 1.46A (35W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$42
PSS24-050	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 2.1A (50W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$47
PSS24-100	RHINO enclosed panel mount switching power supply, 24 VDC (adjustable), 4.17A (100W) output, 85-264 VAC / 100-375 VDC universal input, aluminum case with mounting holes for mounting in two planes, screw terminals, status indication LED. UL60950-1 recognized, CE marked.	\$67
<b>Product Code</b>	<b>RHINO Metal Case Slim-Line Power Supplies and Accessories</b>	<b>Aust\$</b>
PSM12-078S	Switching power supply, 12 VDC (adjustable), 6A, 78W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$288
PSM24-090S	Switching power supply, 24 VDC (adjustable), 3.75A, 90W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$218
PSM24-090S-N	NEC Class 2 switching power supply, 24 VDC (adjustable), 3.75A, 90W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$297
PSM12-156S	Switching power supply, 12 VDC (adjustable), 13A, 156W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$347
PSM24-180S	Switching power supply, 24 VDC (adjustable), 7.5A, 180W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$335
PSM24-360S	Switching power supply, 24 VDC (adjustable), 15A, 360W output, DIN rail mounting, slim, metal case with pluggable screw terminal connector, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$505
PSM24-600S	Switching power supply, 24 VDC (adjustable), 25A, 600W output, DIN rail mounting, slim, metal case, 85-264 VAC auto selectable input, constant current short circuit protection, CSA and CE. Dual color status indicator LED, remote on/off contact and NPN output for operation monitoring. Outputs available for redundancy module. Panel mounting bracket sold separately.	\$748
<b>Product Code</b>	<b>Redundancy Module</b>	<b>Aust\$</b>
PSM24-REM360S	Redundancy module, 24 VDC, 15A, 360W, for use with PSM24 power supplies. Alarm contact for operation monitoring. Inputs are hot swappable and can be loaded to 15A each.	\$353
<b>Product Code</b>	<b>Battery Control Module</b>	<b>Aust\$</b>
PSM24-BCM360S	Battery control module, 24 VDC, 15A, 360W for charging external lead-acid battery. Contacts provided for input and output operation, and battery level. Remote on/off contact and temperature sensing circuit included.	\$349
<b>Product Code</b>	<b>Buffer Module</b>	<b>Aust\$</b>
PSM24-BFM600S	Buffer module, 24 VDC (adjustable), 25A, 600W, for use with PSM power supplies. Provides protection against brownouts or voltage dips on input power. Hold-up time is up to 4 seconds at 1.2A. Operation LED indicator on front panel.	\$505
<b>Product Code</b>	<b>Mounting Bracket</b>	<b>Aust\$</b>
PSM-PANEL1	Panel mounting bracket for 78W, 90W, 156W, 180W PSM power supplies	\$66
PSM-PANEL2	Panel mounting bracket for 360W, 600W PSM power supplies	\$60
PSM-PK1	Replacement plug kit for PSM series with 72W and 90W outputs	\$15
PSM-PK2	Replacement plug kit for PSM series with 156W, 180W and 360W outputs	\$22
PSM-PK4	Replacement plug kit for PSM series buffer module PSM24-BFM600S	\$10
PSM-PK5	Replacement plug kit for PSM series battery control module PSM24-BCM360S	\$40
PSM-TS	Temperature sensor accessory for PSM series battery control module PSM24-BCM360S	\$60
PSM-JC01	Replacement link cable for PSM series redundancy module PSM24-REM360S and battery control module PSM24-BCM360S	\$17

Product Code	RHINO Plastic Case Slim-Line Power Supplies	Aust\$
PSP05-020S	Switching power supply, 5 VDC (adjustable), 4A 20W output, DIN rail or panel mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950, and CE.	\$168
PSP12-024S	Switching power supply, 12 VDC (adjustable), 2A, 24W output, DIN rail or panel mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950, and CE.	\$160
PSP24-024S	Switching power supply, 24 VDC (adjustable), 1A (24W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, foldback short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$122
PSP12-060S	Switching power supply, 12 VDC (adjustable), 4A (60W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$213
PSP24-060S	Switching power supply, 24 VDC (adjustable), 2.5A (60W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$186
PSP12-120S	Switching power supply, 12 VDC (adjustable), 8A (120W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$336
PSP24-120S	Switching power supply, 24 VDC (adjustable), 5A (120W) output, DIN rail mounting, slim, plastic case with pluggable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$297
PSP24-024C	Switching power supply, 24 VDC (adjustable), 1A (24W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, foldback short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$128
PSP12-060C	Switching power supply, 12 VDC (adjustable), 4A (60W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$236
PSP24-060C	Switching power supply, 24 VDC (adjustable), 2.5A (60W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$189
PSP12-120C	Switching power supply, 12 VDC (adjustable), 8A (120W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$275
PSP24-120C	Switching power supply, 24 VDC (adjustable), 5A (120W) output, DIN rail mounting, slim, plastic case with cage clamp terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, 1950 & CE. Plastic DIN rail insert provided for easy panel mounting.	\$314
PSP24-240S	Switching power supply, 24 VDC (adjustable), 10A (120W) output, DIN rail mounting, slim, plastic case with detachable screw terminal connector, 85-264 VAC / 85-375 VDC universal input, constant current short circuit protection, UL508, UL60950 and CE.	\$394
PSP24-REM240S	Redundancy module, 24 VDC, 15A, 360W, for use with PSP24 power supplies. Alarm contact for operation monitoring. Inputs are hot swappable and can be loaded to 15A each.	\$104
Product Code	PS Series Metal Case DC Power Supplies	Aust\$
PS12-050D	Switching power supply, 12 VDC, 4A (50W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-264 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$249
PS12-075D	Switching power supply, 12 VDC, 6A (75W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$362
PS24-050D	Switching power supply, 24 VDC, 2A (50W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-264 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$228
PS24-075D	Switching power supply, 24 VDC, 3A (75W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$254
PS24-150D	Switching power supply, 24 VDC, 6A (150W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$405
PS24-300D	Switching power supply, 24 VDC, 12A (300W) DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$514
PS24-500D	Switching power supply, 24 VDC, 20A (500W) DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC input, constant current short circuit protection, UL508, 1950 & CE.	\$873
PS24-600D	Switching power supply, 24 VDC, 24A (600W) output, DIN rail mounting, metal case with pluggable terminal connector, 93-132 VAC or 187-264 VAC switch selectable input, constant current short circuit protection, UL508, 1950 & CE.	\$891
PS24-PLUG-1	Replacement terminal plug kit for PS12-050D, PS24-050D, PS24-075D and PS24-150D, 1 each input & output plug	\$27
PS24-PLUG-3	Replacement terminal plug kit for PS24-300D, 1 each input & output plug	\$40
PS24-PLUG-5	Replacement terminal plug kit for PS24-500D, 1 each input & output plug	\$36

Product Code	DC to DC Converters	Aust\$
PSP05-DC24-5	DC to DC converter, 18-75 VDC in, 5 VDC at 5.0 amps out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$173
PSP12-DC24-2	DC to DC converter, 18-75 VDC in, 12 VDC at 2.0 amps out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$173
PSP12-DC24-5	DC to DC converter, 18 - 75 VDC input, 12 VDC output, 5A, 60W, plastic housing, 35 mm DIN mount, screw terminal, removable. DIN rail insert for panel mounting included.	\$202
PSP24-DC24-1	DC to DC converter, 18-75 VDC in, 24 VDC at 1.0 amp out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$165
PSP24-DC24-2	DC to DC converter, 18 - 75 VDC input, 24 VDC output, 2.5A, 60W, plastic housing, 35 mm DIN mount, screw terminal, removable. DIN rail insert for panel mounting included.	\$208
PSP24-DC12-1	DC to DC converter, 9.5-18 VDC in, 24 VDC at 1.0 amp out, DIN rail mounting, slim plastic case with detachable screw terminal connector	\$171
FA-DCDC-1	DC to DC converter, 12 - 24 VDC input, +/- 10 VDC, +/-5 VDC output, 0.125A, 3.75W, plastic housing, 35 mm DIN mount, screw terminal, removable.	\$115
	Encapsulated DC to DC Converters	Aust\$
PSE05-DC12-40	DC to DC converter, 9.5 - 36 VDC input, 5.1 VDC output, 8A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$152
PSE12-DC12-40	DC to DC converter, 9.5 - 36 VDC input, 12 VDC output, 3.33A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$152
PSE24-DC12-40	DC to DC converter, 9.5 - 36 VDC input, 24 VDC output, 1.67A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$152
PSE05-DC24-40	DC to DC converter, 18 - 75 VDC input, 5.1 VDC output, 8A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$160
PSE12-DC24-40	DC to DC converter, 18 - 75 VDC input, 12 VDC output, 3.33A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$160
PSE24-DC24-40	DC to DC converter, 18 - 75 VDC input, 24 VDC output, 1.67A, 40W, plastic housing, encapsulated, chassis mount, screw terminal.	\$160
PSE05-DC12-60	DC to DC converter, 9.5 - 36 VDC input, 5.1 VDC output, 12A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$176
PSE12-DC12-60	DC to DC converter, 9.5 - 36 VDC input, 12 VDC output, 5A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$176
PSE24-DC12-60	DC to DC converter, 9.5 - 36 VDC input, 24 VDC output, 2.5A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$176
PSE48-DC12-60	DC to DC converter, 9.5 - 36 VDC input, 48 VDC output, 1.25A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$176
PSE05-DC24-60	DC to DC converter, 18 - 75 VDC input, 5.1 VDC output, 12A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$186
PSE12-DC24-60	DC to DC converter, 18 - 75 VDC input, 12 VDC output, 5A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$186
PSE24-DC24-60	DC to DC converter, 18 - 75 VDC input, 24 VDC output, 2.5A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$186
PSE48-DC24-60	DC to DC converter, 18 - 75 VDC input, 48 VDC output, 1.25A, 60W, plastic housing, encapsulated, chassis mount, screw terminal.	\$186

Product Code	Control Transformers and Accessories	Aust\$
PH50PG	12x24 VAC 50/60 Hz control transformer, 50VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$94
PH75PG	12x24 VAC 50/60 Hz control transformer, 75VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$94
PH100PG	12x24 VAC 50/60 Hz control transformer, 100VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$105
PH150PG	12x24 VAC 50/60 Hz control transformer, 150VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$142
PH250PG	12x24 VAC 50/60 Hz control transformer, 250VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$182
PH350PG	12x24 VAC 50/60 Hz control transformer, 350VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$210
PH500PG	12x24 VAC 50/60 Hz control transformer, 500VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$268
PH750PG	12x24 VAC 50/60 Hz control transformer, 750VA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$356
PH1000PG	12x24 VAC 50/60 Hz control transformer, 1 kVA, 1ph, 120x240 VAC primary, 12x24 VAC secondary; UL, CSA, and CE listed	\$398
PFK1	Primary side fuse kit for control transformers to 100VA	\$15
PFK2	Primary side fuse kit for control transformers from 150VA to 250VA	\$15
PFK3	Primary side fuse kit for control transformers from 350VA to 1KVA	\$15
FG1	Finger-safe cover for 50VA UNFUSED control transformers, includes one cover for primary side or secondary side	\$12
FG2	Finger-safe cover for 75VA and 100VA UNFUSED control transformers, includes one cover for primary side or secondary side	\$12
FGF1	Finger-safe cover for 50VA FUSED control transformers, includes one cover for primary side or secondary side	\$12
FGF2	Finger-safe cover for 75VA and 100VA FUSED control transformers, includes one cover for primary side or secondary side	\$12
FG3	Finger-safe cover for all 150VA and 250VA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side	\$12
FG4	Finger-safe cover for all 350VA and 750VA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side.	\$12
FG5	Finger-safe cover for all 1kVA FUSED and UNFUSED control transformers, includes one cover for primary side or secondary side	\$12