

Sensor & Input Devices		
Proximity Switches		
Product Code	8mm Round (Standard)	Aust\$
AE1-AN-1A	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$55
AE1-AN-2A	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, 2 meter cable exit	\$55
AE1-AN-1F	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$55
AE1-AN-2F	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$55
AE1-AN-1H	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AE1-AN-2H	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AE1-AP-1A	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$55
AE1-AP-2A	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, 2 meter cable exit	\$55
AE1-AP-1F	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$55
AE1-AP-2F	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$55
AE1-AP-1H	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 1.5 mm nominal sensing distance, normally open output, 3kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AE1-AP-2H	Proximity sensor, 8 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 2.5 mm nominal sensing distance, normally open output, 2.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
Product Code	8mm Round (Extended)	Aust\$
AE1-AN-3A	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 2 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$68
AE1-AN-4A	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 4 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$68
AE1-AN-3F	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 2 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$68
AE1-AN-4F	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 4 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$68
AE1-AP-3A	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 2 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$68
AE1-AP-4A	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 4 mm nominal sensing distance, normally open output, 3kHz switching frequency, 2 meter cable exit	\$68
AE1-AP-3F	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 2 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$68
AE1-AP-4F	Proximity sensor, 8 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 4 mm nominal sensing distance, normally open output, 3kHz switching frequency, M8 quick-disconnect (purchase cable separately)	\$68
Product Code	12mm Round (Standard)	Aust\$
AM1-AN-1A	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 2 mm nominal sensing distance, normally open output, 2kHz switching frequency, 2 meter cable exit	\$53
AM1-AN-2A	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 4 mm nominal sensing distance, normally open output, 2kHz switching frequency, 2 meter cable exit	\$53
AM1-AN-1H	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 2 mm nominal sensing distance, normally open output, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$53
AM1-AN-2H	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 4 mm nominal sensing distance, normally open output, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$53
AM1-AP-1A	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 2 mm nominal sensing distance, normally open output, 2kHz switching frequency, 2 meter cable exit	\$53
AM1-AP-2A	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 4 mm nominal sensing distance, normally open output, 2kHz switching frequency, 2 meter cable exit	\$53

AM1-AP-1H	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 2 mm nominal sensing distance, normally open output, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$53
AM1-AP-2H	Proximity sensor, 12 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 4 mm nominal sensing distance, normally open output, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$53
AM1-A0-1A	Proximity sensor, 12 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 2 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, 2 meter cable exit	\$58
AM1-A0-2A	Proximity sensor, 12 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 4 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, 2 meter cable exit	\$58
AM1-A0-1H	Proximity sensor, 12 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 2 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$58
AM1-A0-2H	Proximity sensor, 12 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 4 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$58
Product Code	12mm Round (Extended)	Aust\$
AM1-AN-3A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 4 mm nominal sensing distance, normally open output, 1kHz switching frequency, 2 meter cable exit	\$65
AM1-AN-4A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 8 mm nominal sensing distance, normally open output, 1kHz switching frequency, 2 meter cable exit	\$65
AM1-AN-3H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 4 mm nominal sensing distance, normally open output, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$65
AM1-AN-4H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 8 mm nominal sensing distance, normally open output, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$65
AM1-AP-3A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 4 mm nominal sensing distance, normally open output, 1kHz switching frequency, 2 meter cable exit	\$65
AM1-AP-4A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 8 mm nominal sensing distance, normally open output, 1kHz switching frequency, 2 meter cable exit	\$65
AM1-AP-3H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 4 mm nominal sensing distance, normally open output, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$65
AM1-AP-4H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 8 mm nominal sensing distance, normally open output, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$65
AM1-A0-3A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 4 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, 2 meter cable exit	\$71
AM1-A0-4A	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 8 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, 2 meter cable exit	\$71
AM1-A0-3H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 4 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$71
AM1-A0-4H	Proximity sensor, 12 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 8 mm nominal sensing distance, normally open output, 1.5kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$71
Product Code	12mm Round (Stainless Steel)	Aust\$
PMW-0N-1H	Proximity sensor, 12 mm diameter, stainless steel, 10-30 VDC, 4-wire, NPN, shielded, 2 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$108
PMW-0N-2H	Proximity sensor, 12 mm diameter, stainless steel, 10-30 VDC, 4-wire, NPN, unshielded, 4 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$108

PMW-0P-1H	Proximity sensor, 12 mm diameter, stainless steel, 10-30 VDC, 4-wire, PNP, shielded, 2 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$108
PMW-0P-2H	Proximity sensor, 12 mm diameter, stainless steel, 10-30 VDC, 4-wire, PNP, unshielded, 4 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$108
Product Code	12mm Round (AC-Powered)	Aust\$
VM1-A0-1B	Proximity sensor, 12 mm diameter, 20-253 VAC, shielded, 2 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$100
VM1-A0-2B	Proximity sensor, 12 mm diameter, 20-253 VAC, unshielded, 4 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$100
VM1-A0-1H	Proximity sensor, 12 mm diameter, 20-253 VAC, shielded, 2 mm nominal sensing distance, normally open output, 25Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$100
VM1-A0-2H	Proximity sensor, 12 mm diameter, 20-253 VAC, unshielded, 4 mm nominal sensing distance, normally open output, 25Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$100
Product Code	12mm Round (with IP69K Harsh Duty Rating)	Aust\$
PFM1-BN-1H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 2mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BN-2H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BN-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BN-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-AP-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 4mm nominal sensing distance, normally open output, 800Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$100
PFM1-AP-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 7mm nominal sensing distance, normally open output, 800Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$100
PFM1-BP-1H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 2mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BP-2H	Proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BP-3H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 4mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
PFM1-BP-4H	Proximity sensor, 12mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 2kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$119
Product Code	18mm Round (Standard)	Aust\$
AK1-AN-1A	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, 2 meter cable exit	\$55
AK1-AN-2A	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$55

AK1-AN-1H	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AK1-AN-2H	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AK1-AP-1A	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, 2 meter cable exit	\$55
AK1-AP-2A	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$55
AK1-AP-1H	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AK1-AP-2H	Proximity sensor, 18 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$55
AK1-A0-1A	Proximity sensor, 18 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, 2 meter cable exit	\$59
AK1-A0-2A	Proximity sensor, 18 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$59
AK1-A0-1H	Proximity sensor, 18 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 5 mm nominal sensing distance, normally open output, 600Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$59
AK1-A0-2H	Proximity sensor, 18 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$59
Product Code	18mm Round (Extended)	Aust\$
AK1-AN-3A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$68
AK1-AN-4A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$68
AK1-AN-3H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$68
AK1-AN-4H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$68
AK1-AP-3A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$68
AK1-AP-4A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$68
AK1-AP-3H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$68
AK1-AP-4H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$68
AK1-A0-3A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$76
AK1-A0-4A	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, 2 meter cable exit	\$76
AK1-A0-3H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 8 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$76
AK1-A0-4H	Proximity sensor, 18 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 12 mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$76

Product Code	18mm Round (Stainless Steel)	Aust\$
PKW-0N-1H	Proximity sensor, 18 mm diameter, stainless steel, 10-30 VDC, 4-wire, NPN, shielded, 5 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$117
PKW-0N-2H	Proximity sensor, 18 mm diameter, stainless steel, 10-30 VDC, 4-wire, NPN, unshielded, 8 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$117
PKW-0P-1H	Proximity sensor, 18 mm diameter, stainless steel, 10-30 VDC, 4-wire, PNP, shielded, 5 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$117
PKW-0P-2H	Proximity sensor, 18 mm diameter, stainless steel, 10-30 VDC, 4-wire, PNP, unshielded, 8 mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1kHz switching frequency, M12 quick-disconnect (purchase cable separately)	\$117
Product Code	18mm Round (Stainless Steel/Superior)	Aust\$
PKW-AN-5A	Proximity sensor, 18 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, NPN, submersible to 290psi, 10 mm sensing distance (on most metals), normally open output, 200Hz switching frequency, 2 meter cable exit	\$264
PKW-AN-5H	Proximity sensor, 18 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, NPN, submersible to 290psi, 10 mm sensing distance (on most metals), normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$191
PKW-AP-5A	Proximity sensor, 18 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, PNP, submersible to 290psi, 10 mm sensing distance (on most metals), normally open output, 200Hz switching frequency, 2 meter cable exit	\$191
PKW-AP-5H	Proximity sensor, 18 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, PNP, submersible to 290psi, 10 mm sensing distance (on most metals), normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$191
Product Code	18mm Round (AC-Powered)	Aust\$
VK1-A0-1B	Proximity sensor, 18 mm diameter, 20-253 VAC, shielded, 5 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$88
VK1-A0-2B	Proximity sensor, 18 mm diameter, 20-253 VAC, unshielded, 8 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$88
Product Code	18mm Round (with IP69K Harsh Duty Rating)	Aust\$
PFK1-BN-1H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 5mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
PFK1-BN-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, shielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
PFK1-BN-2H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
PFK1-BN-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, NPN, unshielded, 12mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$153
PFK1-AP-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 8mm nominal sensing distance, normally open output, 600Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$100
PFK1-BP-1H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 5mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
PFK1-BP-3H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, shielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$151
PFK1-AP-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 12mm nominal sensing distance, normally open output, 300Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$107

PFK1-BP-2H	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 8mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
PFK1-BP-4H	Proximity sensor, 18mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PPS sensing face, 10-30 VDC, 4-wire, PNP, unshielded, 12mm nominal sensing distance, complementary (N.O. or N.C.) outputs, 1.5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$153
Product Code	18mm Round (AC Powered with IP69K Harsh Duty Rating)	Aust\$
VFK1-A0-1M	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, shielded, 5mm nominal sensing distance, normally open output, 25Hz (AC) / 400Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$153
VFK1-A0-2M	Proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, unshielded, 12mm nominal sensing distance, normally open output, 25Hz (AC) / 300Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$166
Product Code	30mm Round (Standard)	Aust\$
AT1-AN-1A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 10 mm nominal sensing distance, normally open output, 200Hz switching frequency, 2 meter cable exit	\$69
AT1-AN-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 15 mm nominal sensing distance, normally open output, 200Hz switching frequency, 2 meter cable exit	\$69
AT1-AN-1H	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, 10 mm nominal sensing distance, normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$69
AT1-AN-2H	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, 15 mm nominal sensing distance, normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$69
AT1-AP-1A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 10 mm nominal sensing distance, normally open output, 200Hz switching frequency, 2 meter cable exit	\$69
AT1-AP-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 15 mm nominal sensing distance, normally open output, 200Hz switching frequency, 2 meter cable exit	\$69
AT1-AP-1H	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, 10 mm nominal sensing distance, normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$69
AT1-AP-2H	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, 15 mm nominal sensing distance, normally open output, 200Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$69
AT1-A0-1A	Proximity sensor, 30 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 10 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$89
AT1-A0-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$89
AT1-A0-1H	Proximity sensor, 30 mm diameter, 10-30 VDC, 2-wire, sink/source, shielded, 10 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$99
AT1-A0-2H	Proximity sensor, 30 mm diameter, 10-30 VDC, 2-wire, sink/source, unshielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$99
Product Code	30mm Round (Extended)	Aust\$
AT1-AN-3A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$87
AT1-AN-4A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$87
AT1-AN-3H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$87

AT1-AN-4H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, NPN, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$87
AT1-AP-3A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$87
AT1-AP-4A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$87
AT1-AP-3H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$87
AT1-AP-4H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 3-wire, PNP, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$87
AT1-A0-3A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$98
AT1-A0-4A	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, 2 meter cable exit	\$98
AT1-A0-3H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, shielded, 15 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$98
AT1-A0-4H	Proximity sensor, 30 mm diameter, extended range, 10-30 VDC, 2-wire, sink/source, unshielded, 20 mm nominal sensing distance, normally open output, 150Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$98
Product Code	30mm Round (Stainless Steel/Superior)	Aust\$
PTW-AN-5A	Proximity sensor, 30 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, NPN, submersible to 290 psi, 20 mm sensing distance (on most metals), normally open output, 100Hz switching frequency, 2 meter cable exit	\$229
PTW-AP-5A	Proximity sensor, 30 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, PNP, submersible to 290 psi, 20 mm sensing distance (on most metals), normally open output, 100Hz switching frequency, 2 meter cable exit	\$229
PTW-AN-5H	Proximity sensor, 30 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, NPN, submersible to 290 psi, 20 mm sensing distance (on most metals), normally open output, 100Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$229
PTW-AP-1H	Proximity sensor, 30mm diameter, full 316L stainless steel body and sensing face, 10-36 VDC, 3-wire, PNP, shielded, 10mm nominal sensing distance, normally open output, 50Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$138
PTW-AP-5H	Proximity sensor, 30 mm diameter, extra extended sensing, stainless steel (1-piece), 10-30 VDC, 3-wire, PNP, submersible to 290 psi, 20 mm sensing distance (on most metals), normally open output, 100Hz switching frequency, M12 quick-disconnect (purchase cable separately)	\$219
Product Code	30mm Round (AC Powered)	Aust\$
VT1-A0-1B	Proximity sensor, 30 mm diameter, 20-253 VAC, shielded, 10 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$105
VT1-A0-2B	Proximity sensor, 30 mm diameter, 20-253 VAC, unshielded, 15 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2 meter cable exit	\$105
Product Code	30mm Round (with IP69K Harsh Duty Rating)	Aust\$
PFT1-AP-3H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel short housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 14mm nominal sensing distance, normally open output, 50Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$128
PFT2-AP-3H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 15mm nominal sensing distance, normally open output, 50Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$128
PFT1-AP-4H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel short housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 100Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$128
PFT2-AP-4H	Proximity sensor, 30mm diameter, extended range, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 100Hz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$128

Product Code	30mm Round (AC-Powered/with IP69K Harsh Duty Rating)	Aust\$
VFT1-A0-1M	Proximity sensor, 30mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, shielded, 14mm nominal sensing distance, normally open output, 25Hz (AC) / 100Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$164
VFT1-A0-2M	Proximity sensor, 30mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 20-140 VAC/VDC, 2-wire, PNP, unshielded, 22mm nominal sensing distance, normally open output, 25Hz (AC) / 100Hz (DC) switching frequency, 1/2 inch micro AC quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$164
Product Code	30mm Round (Capacitive)	Aust\$
CT1-AN-1A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, shielded, adjustable 2 - 15 mm nominal sensing distance, normally open output, 100Hz switching frequency, 2 meter cable exit	\$195
CT1-AN-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, adjustable 2 - 20 mm nominal sensing distance, normally open output, 100Hz switching frequency, 2 meter cable exit	\$195
CT1-CN-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, NPN, unshielded, adjustable 2 - 20 mm nominal sensing distance, normally closed output, 100Hz switching frequency, 2 meter cable exit	\$195
CT1-AP-1A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, shielded, adjustable 2 - 15 mm nominal sensing distance, normally open output, 100Hz switching frequency, 2 meter cable exit	\$195
CT1-AP-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, adjustable 2 - 20 mm nominal sensing distance, normally open output, 100Hz switching frequency, 2 meter cable exit	\$195
CT1-CP-2A	Proximity sensor, 30 mm diameter, 10-30 VDC, 3-wire, PNP, unshielded, adjustable 2 - 20 mm nominal sensing distance, normally closed output, 100Hz switching frequency, 2 meter cable exit	\$195
Product Code	18mm Round (Ultrasonic/1500mm max sensing range)	Aust\$
SU1-B0-0A	Ultrasonic proximity sensor, 18mm diameter, 15-30 VDC, 4-wire, PNP, 100-600 mm nominal sensing distance, normally open output, 25Hz switching frequency, 2-meter cable exit	\$794
SU1-B1-0A	Ultrasonic, 18 mm diameter, 18-30 VDC, 0-10 VDC output, 100-600 mm nominal sensing distance, M12 quick-disconnect (purchase cable separately)	\$794
SU1-B1-0E	Ultrasonic, 18 mm diameter, 15-30 VDC, PNP, 200-1,500 mm nominal sensing distance, normally open output, 8Hz switching frequency, 2 meter cable exit	\$794
SU2-A0-0A	Ultrasonic, 18 mm diameter, 18-30 VDC, 0-10 VDC output, 200-1,500 mm nominal sensing distance, M12 quick-disconnect (purchase cable separately)	\$794
SU2-A1-0E	Ultrasonic proximity sensor, 18mm diameter, 18-30 VDC, 4-wire, 0-10 VDC analog output, 200-1500 mm nominal sensing distance, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$794
Product Code	Magnetic Sensors (with IP69K Harsh Duty Rating) and Accessories	Aust\$
MAFM1-A0-1H	Magnetic proximity sensor, 12mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 60mm nominal sensing distance, normally open output, 5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$125
MAFK1-A0-1H	Magnetic proximity sensor, 18mm diameter, IP69K for harsh duty / food and beverage applications, 316L stainless steel housing, FDA certified PEEK sensing face, 10-30 VDC, 3-wire, PNP, shielded, 70mm nominal sensing distance, normally open output, 5kHz switching frequency, M12 quick-disconnect. Mounting hex nuts included. Purchase cable separately.	\$139
AW-MAG	Damping magnet, Barium ferrite with 316L stainless steel coating, use with MAFM1 and MAFK1 series sensors	\$100
Part	Koyo Mini Rectangular Sensors	
APS4-12S-E-D	Proximity sensor, 12 mm x 27 mm x 7 mm rectangular, 10-30 VDC, NPN, unshielded, 4 mm sensing distance, normally open output, 2 meter cable exit	\$39
APS4-12M-E-D	Proximity sensor, 12 mm x 27 mm x 12 mm rectangular, 10-30 VDC, NPN, unshielded, 4 mm sensing distance, normally open output, 2 meter cable exit	\$39
APS4-12S-E2-D	Proximity sensor, 12 mm x 27 mm x 7 mm rectangular, 10-30 VDC, PNP, unshielded, 4 mm sensing distance, normally open output, 2 meter cable exit	\$39
APS4-12M-E2-D	Proximity sensor, 12 mm x 27 mm x 12 mm rectangular, 10-30 VDC, PNP, unshielded, 4 mm sensing distance, normally open output, 2 meter cable exit	\$39
Product Code	3-Pole Pico (M8) Sensor Cables	Aust\$
CD08-0A-020-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 2 meter length, gray PVC outer jacket	\$24
CD08-0A-020-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 2 meter length, gray PVC outer jacket	\$24
CD08-0C-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 5 meter length, black PUR outer jacket	\$26

CD08-0C-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 5 meter length, black PUR outer jacket	\$26
CD08-0A-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 5 meter length, black PVC outer jacket	\$24
CD08-0A-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 5 meter length, black PVC outer jacket	\$24
CD08-0A-070-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 3-pole, 7 meter length, gray PVC outer jacket	\$38
CD08-0A-070-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 3-pole, 7 meter length, gray PVC outer jacket	\$38
CDP08-0A-010-AA	M8 patch cable with 8mm axial 3-pole female plug to 8mm axial 3-pole male plug, 1 meter length, gray PVC outer jacket	\$24
CDP08-0A-030-AA	M8 patch cable with 8mm axial 3-pole female plug to 8mm axial 3-pole male plug, 3 meter length, gray PVC outer jacket	\$29
CDP08-0A-010-BB	M8 patch cable with 8mm right angle 3-pole female plug to 8mm right angle 3-pole male plug, 1 meter length, gray PVC outer jacket	\$24
CDP08-0A-030-BB	M8 patch cable with 8mm right angle 3-pole female plug to 8mm right angle 3-pole male plug, 3 meter length, gray PVC outer jacket	\$24
Product Code	4-Pole Pico (M8) Sensor Cables	Aust\$
CD08-0G-020-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 2 meter length, black PVC outer jacket Use with DFP/DFT models.	\$20
CD08-0G-050-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 5 meter length, black PVC outer jacket Use with DFP/DFT models.	\$24
CD08-0G-100-A1	M8 cable for quick-disconnect sensors, 8mm axial female plug, 4-pole, 10 meter length, black PVC outer jacket Use with DFP/DFT models.	\$30
CD08-0W-020-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 2 meter length, black PVC outer jacket Use with DFP/DFT models.	\$20
CD08-0W-050-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 5 meter length, black PVC outer jacket Use with DFP/DFT models.	\$24
CD08-0W-100-C1	M8 cable for quick-disconnect sensors, 8mm right angle female plug, 4-pole, 10 meter length, black PVC outer jacket Use with DFP/DFT models.	\$30
Product Code	3-Pole Micro (M12) Sensor Cables	Aust\$
CD12M-0B-050-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 3-pole, 5 meter length, black PVC outer jacket. Do not use with SU and TU series sensors.	\$24
CD12M-0D-050-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 3-pole, 5 meter length, black PUR outer jacket. Do not use with SU and TU series sensors.	\$29
CD12M-0D-050-C1	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 3-pole, 5 meter length, black PUR outer jacket. Do not use with SU and TU series sensors.	\$29
Product Code	4-Pole Micro (M12) Sensor Cables	
CD12L-0B-020-A0	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 2 meter length, gray PVC outer jacket	\$24
CD12L-0B-020-C0	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 2 meter length, gray PVC outer jacket	\$24
CD12M-0B-070-A1	M12 cable for quick-disconnect sensors, 12mm axial female plug, 4-pole, 7 meter length, gray PVC outer jacket	\$38
CD12M-0B-070-C1	M12 cable for quick-disconnect sensors, 12mm right-angle female plug, 4-pole, 7 meter length, gray PVC outer jacket	\$38

CDP12-0B-010-AA	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, 1 meter length, gray PVC jacket	\$44
CDP12-0B-030-AA	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, 3 meter length, gray PVC jacket	\$44
CDP12-0B-010-BB	M12 patch cable, 12mm right angle 4-pole female plug to 12mm right angle 4-pole male plug, 1 meter length, gray PVC jacket	\$59
CDP12-0B-030-BB	M12 patch cable, 12mm right angle 4-pole female plug to 12mm right angle 4-pole male plug, 3 meter length, gray PVC jacket	\$59
Product Code	Micro (M12) Harsh Duty Sensor Cables	Aust\$
EVT221	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$37
EVT222	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$37
EVT223	M12 cable for quick-disconnect sensors, 12mm axial female, IP69K rated, stainless steel plug, 4-pole, 10-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$51
EVT224	M12 cable for quick-disconnect sensors, 12mm right angle female, IP69K rated, stainless steel plug, 4-pole, 10-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$51
EVT225	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.3-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$45
EVT226	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.3-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$48
EVT227	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.6-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$50
EVT228	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 0.6-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$54
EVT229	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 1-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$62
EVT230	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 1-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$45
EVT231	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 2-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$48
EVT232	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 2-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$50
EVT233	M12 patch cable, 12mm axial 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$54
EVT234	M12 patch cable, 12mm right angle 4-pole female plug to 12mm axial 4-pole male plug, IP69K rated, stainless steel connection , 5-meter cable, orange PVC outer jacket suitable for food and beverage applications	\$62
E18446	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 5 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$63
E18447	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 5 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$78
E18448	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch axial female, IP69K rated, stainless steel plug, 3-pole, 10 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$63
E18449	Micro AC volt 1/2 inch - 20UNF cable for quick-disconnect AC volt sensors, 1/2 inch right angle female, IP69K rated, stainless steel plug, 3-pole, 10 meter length, yellow PVC outer jacket suitable for food and beverage applications	\$78
Product Code	Sensors Mounting Brackets	Aust\$
ST12A	Mounting bracket for 12 mm sensors, metal, axial, qty. 1	\$6

ST12C	Mounting bracket for 12 mm sensors, metal, right angle, qty. 1	\$6
ST18A	Mounting bracket for 18 mm sensors, metal, axial, qty. 1	\$4
ST18C	Mounting bracket for 18 mm sensors, metal, right angle, qty. 1	\$4
ST30A	Mounting bracket for 30 mm sensors, metal, axial, qty. 1	\$7
ST30C	Mounting bracket for 30 mm sensors, metal, right angle, qty. 1	\$7
ST12A7W	Mounting bracket for 12mm sensors, 316L stainless steel metal for harsh duty / food and beverage applications, axial, 1 per pack	\$17
ST12C7W	Mounting bracket for 12mm sensors, 316L stainless steel metal for harsh duty / food and beverage applications, right angle, 1 per pack	\$17
ST18A7W	Mounting bracket for 18mm sensors, 316L stainless steel metal for harsh duty / food and beverage applications, axial, 1 per pack	\$17
ST18C7W	Mounting bracket for 18mm sensors, 316L stainless steel metal for harsh duty / food and beverage applications, right angle, 1 per pack	\$17
GXM3GD2340	Hexnuts for 8 mm proximity sensors, pack of 6	\$9
GXM31D2474	Hexnuts for 12 mm proximity sensors, pack of 6	\$18
GXM3PD2013	Hexnuts for 30 mm proximity sensors, pack of 6	\$31