

Motor Controls		
Relays & Timers		
Slimline 6mm Relays		Aust\$
KPR-SCF-230VAC-1	Slim 6mm Relay 230VAC/230 VAC coil voltage, SPDT, 6A contact rating, screw terminal(s), LED indicator(s). Integrated leakage current suppression filter.	\$15
KPR-SCF-115VACDC-1	Slim 6mm Relay 115VAC/VDC/115 VAC/VDC coil voltage, SPDT, 6A contact rating, screw terminal(s), LED indicator(s). Integrated leakage current suppression filter.	\$15
KPR-SCE-12VACDC-1	Slim 6mm Relay 12VAC/VDC/12 VAC/VDC coil voltage, SPDT, 6A contact rating, screw terminal(s), LED indicator(s).	\$15
KPR-SCE-24VACDC-1	Slim 6mm Relay 24VAC/VDC/24 VAC/VDC coil voltage, SPDT, 6A contact rating, screw terminal(s), LED indicator(s).	\$15
APP-KPR	Slim 6mm Separator Plate Orange. Package of 5. For use with all KPR-SCF-x or KPR-SCE-x interface relays.	\$8
TK-KPR-S16	Slim 6mm Jumper 16p Push-in type, 16-pole, black. Package of 5. For use with all KPR-SCF-x or KPR-SCE-x interface relays.	\$25
TK-KPR-S8	Slim 6mm Jumper 8P Push-in type, 8-pole, black. Package of 5. For use with all KPR-SCF-x or KPR-SCE-x interface relays.	\$16
Product Code	Q Series Electromechanical Cube Relays and Accessories	Aust\$
QM2N1-A220	Ice cube control relay, 240VAC coil, DPDT, 5A contact rating, with LED indicator. Purchase SQM08D mounting socket separately.	\$12
QM4N1-A120	Ice cube control relay, 120VAC coil, 4PDT, 3A contact rating, with LED indicator. Purchase SQM14D mounting socket separately.	\$12
QM4X1-D24	Ice cube control relay, 24VDC coil, 4PDT, 3A contact rating, with LED indicator and diode protection. Purchase SQM14D mounting socket separately.	\$22
QM4N1-A220	Ice cube control relay, 240VAC coil, 4PDT, 3A contact rating, with LED indicator. Purchase SQM14D mounting socket separately.	\$20
QL2N1-D24	Ice cube control relay, 24VDC coil, DPDT, 10A contact rating, with LED indicator. Purchase SQL08D mounting socket separately.	\$25
QL2X1-D24	Ice cube control relay, 24VDC coil, DPDT, 10A contact rating, with LED indicator and diode protection. Purchase SQL08D mounting socket separately.	\$29
QL4N1-A120	Ice cube control relay, 120VAC coil, 4PDT, 10A contact rating, with LED indicator. Purchase SQL14D mounting socket separately.	\$29
QL4N1-D24	Ice cube control relay, 24VDC coil, 4PDT, 10A contact rating, with LED indicator. Purchase SQL14D mounting socket separately.	\$28
QL4X1-D24	Ice cube control relay, 24VDC coil, 4PDT, 10A contact rating, with LED indicator and diode protection. Purchase SQL14D mounting socket separately.	\$37
QL4N1-A220	Ice cube control relay, 240VAC coil, 4PDT, 10A contact rating, with LED indicator. Purchase SQL14D mounting socket separately.	\$30
SQL08D	Relay socket for QL2 series relays, 35mm DIN-rail or panel mount	\$10
SQL14D	Relay socket for QL4 series relays, 35mm DIN-rail or panel mount	\$11
SQM08D	Relay socket for QM2 series relays, 35mm DIN-rail or panel mount	\$9
Product Code	78 Series Electromechanical Cube Relays and Accessories	Aust\$
781-1C-12D	Ice cube control relay, 12 VDC coil voltage, SPDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 781-1C-SKT mounting socket separately.	\$10
781-1C-12A	Ice cube control relay, 12 VAC coil voltage, SPDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 781-1C-SKT mounting socket separately.	\$10
781-1C-24D	Cube relay, 24 VDC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button	\$10
781-1C-24A	Cube relay, 24 VAC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button	\$10
781-1C-120A	Cube relay, 120 VAC coil voltage, 1PDT, 15A contact rating, with LED indicator and push-to-test button	\$10
781-1C-240A	Cube relay, 240 VAC coil voltage, 1PDT, 12A contact rating, with LED indicator and push-to-test button	\$12
782-2C-12D	Ice cube control relay, 12 VDC coil voltage, DPDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 782-2C-SKT mounting socket separately.	\$12
782-2C-12A	Ice cube control relay, 12 VAC coil voltage, DPDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 782-2C-SKT mounting socket separately.	\$12
782-2C-24D	Cube relay, 24 VDC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button	\$12
782-2C-24A	Cube relay, 24 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button	\$13
782-2C-120A	Cube relay, 120 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button	\$13
782-2C-240A	Cube relay, 240 VAC coil voltage, 2PDT, 15A contact rating, with LED indicator and push-to-test button	\$14
783-3C-12D	Ice cube control relay, 12 VDC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 783-3C-SKT mounting socket separately.	\$13
783-3C-12A	Ice cube control relay, 12 VAC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 783-3C-SKT mounting socket separately.	\$17
783-3C-24D	Cube relay, 24 VDC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button	\$18
783-3C-24A	Cube relay, 24 VAC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button	\$18
783-3C-120A	Cube relay, 120 VAC coil voltage, 3PDT, 15A contact rating, with LED indicator and push-to-test button	\$18

783-3C-240A	Cube relay, 240 VAC coil voltage, 3PDT, 12A contact rating, with LED indicator and push-to-test button	\$18
784-4C-12D	Ice cube control relay, 12 VDC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 784-4C-SKT-1 mounting socket separately.	\$16
784-4C-12A	Ice cube control relay, 12 VAC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button. Purchase 784-4C-SKT-1 mounting socket separately.	\$21
784-4C-24D	Cube relay, 24 VDC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button	\$17
784-4C-24A	Cube relay, 24 VAC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button	\$17
784-4C-120A	Cube relay, 120 VAC coil voltage, 4PDT, 15A contact rating, with LED indicator and push-to-test button	\$17
784-4C-240A	Cube relay, 240 VAC coil voltage, 4PDT, 12A contact rating, with LED indicator and push-to-test button	\$17
781-1C-SKT	DIN-rail socket for 781 series cube relays	\$9
782-2C-SKT	DIN-rail socket for 782 and AD-70S2 series cube relays	\$9
783-3C-SKT	DIN-rail socket for 783 series cube relays	\$10
784-4C-SKT-1	DIN-rail socket for 784 series cube relays	\$11
	OCTAL CONTROL RELAY	Aust\$
750R-2C-12D	Octal control relay, 12VDC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$18
750R-2C-12A	Octal control relay, 12VAC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$21
750R-2C-24D	Octal control relay, 24VDC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$18
750R-2C-24A	Octal control relay, 24VAC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$18
750R-2C-120A	Octal control relay, 120VAC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$18
750R-2C-240A	Octal control relay, 240VAC coil voltage, DPDT, 10A contact rating, 8-pin configuration, with LED indicator and push-to-test button. Purchase 750-2C-SKT mounting socket separately.	\$20
750R-3C-12D	Octal control relay, 12VDC coil voltage, 3PDT, 10A contact rating, 11-pin configuration, with LED indicator and push-to-test button. Purchase 750-3C-SKT mounting socket separately.	\$20
750R-3C-24D	Octal control relay, 24VDC coil voltage, 3PDT, 10A contact rating, 11-pin configuration, with LED indicator and push-to-test button. Purchase 750-3C-SKT mounting socket separately.	\$20
750R-3C-24A	Octal control relay, 24VAC coil voltage, 3PDT, 10A contact rating, 11-pin configuration, with LED indicator and push-to-test button. Purchase 750-3C-SKT mounting socket separately.	\$21
750R-3C-120A	Octal control relay, 120VAC coil voltage, 3PDT, 10A contact rating, 11-pin configuration, with LED indicator and push-to-test button. Purchase 750-3C-SKT mounting socket separately.	\$21
750R-3C-240A	Octal control relay, 240VAC coil voltage, 3PDT, 10A contact rating, 11-pin configuration, with LED indicator and push-to-test button. Purchase 750-3C-SKT mounting socket separately.	\$22
Product Code	Electromechanical Relay Accessories	Aust\$
750-2C-SKT	DIN-rail socket for 750-2C series octal relays, 8-pin configuration	\$10
750-3C-SKT	DIN-rail socket for 750-3C and 755 series octal relays, 11-pin configuration	\$11
33-796-1	Bus bar used to connect multiple octal relays in parallel. Package includes 5 pair of bus bars to connect up to 5 relays together.	\$7
Product Code	78 and 75 Series Electromechanical Relay Accessories	Aust\$
AD-ASMD-250	Protection diode module for 784 and 750 series relays. Package includes 5 modules.	\$22
AD-BSMD-250	Protection diode module for 782 series relays. Package includes 5 modules.	\$18
AD-ASMM-24	MOV module for 784 and 750 series relays that operate at 24 VAC coil voltage. Package includes 5 modules.	\$18
AD-ASMM-120	MOV module for 784 and 750 series relays that operate at 120 VAC coil voltage. Package includes 5 modules.	\$18
AD-ASMM-240	MOV module for 784 and 750 series relays that operate at 240 VAC coil voltage. Package includes 5 modules.	\$18
AD-BSMM-24	MOV module for 782 series relays that operate at 24 VAC coil voltage. Package includes 5 modules.	\$18
AD-BSMM-120	MOV module for 782 series relays that operate at 120 VAC coil voltage. Package includes 5 modules.	\$18
AD-BSMM-240	MOV module for 782 series relays that operate at 240 VAC coil voltage. Package includes 5 modules.	\$18

Product Code	H782 Series Cube Relays	
H782-4C3-12D	Ice cube control relay, hermetically sealed for hazardous locations, 12 VDC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$77
H782-4C3-12A	Ice cube control relay, hermetically sealed for hazardous locations, 12 VAC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$77
H782-4C3-24D	Ice cube control relay, hermetically sealed for hazardous locations, 24 VDC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$77
H782-4C3-24A	Ice cube control relay, hermetically sealed for hazardous locations, 24 VAC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$77
H782-4C3-120A	Ice cube control relay, hermetically sealed for hazardous locations, 120 VAC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$89
H782-4C3-240A	Ice cube control relay, hermetically sealed for hazardous locations, 240 VAC coil voltage, 4PDT, 3A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$89
H782-4C5-12D	Ice cube control relay, hermetically sealed for hazardous locations, 12 VDC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$78
H782-4C5-12A	Ice cube control relay, hermetically sealed for hazardous locations, 12 VAC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$85
H782-4C5-24D	Ice cube control relay, hermetically sealed for hazardous locations, 24 VDC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$78
H782-4C5-24A	Ice cube control relay, hermetically sealed for hazardous locations, 24 VAC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$81
H782-4C5-120A	Ice cube control relay, hermetically sealed for hazardous locations, 120 VAC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$87
H782-4C5-240A	Ice cube control relay, hermetically sealed for hazardous locations, 240 VAC coil voltage, 4PDT, 5A contact rating. Purchase 782-4C-SKT mounting socket separately.	\$93
782-4C-SKT	Relay socket for H782 series cube relays, 35mm DIN-rail or panel mount	\$8
Product Code	H750 Series Octal Relays	Aust\$
H750-2C-12D	Octal control relay, hermetically sealed for hazardous locations, 12 VDC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$99
H750-2C-12A	Octal control relay, hermetically sealed for hazardous locations, 12 VAC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$105
H750-2C-24D	Octal control relay, hermetically sealed for hazardous locations, 24 VDC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$99
H750-2C-24A	Octal control relay, hermetically sealed for hazardous locations, 24 VAC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$105
H750-2C-120A	Octal control relay, hermetically sealed for hazardous locations, 120 VAC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$105
H750-2C-240A	Octal control relay, hermetically sealed for hazardous locations, 240 VAC coil voltage, DPDT, 12A contact rating, 8-pin configuration. Purchase 750-2C-SKT mounting socket separately.	\$119
H750-3C-12D	Octal control relay, hermetically sealed for hazardous locations, 12 VDC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$111
H750-3C-12A	Octal control relay, hermetically sealed for hazardous locations, 12 VAC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$111
H750-3C-24D	Octal control relay, hermetically sealed for hazardous locations, 24 VDC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$106
H750-3C-24A	Octal control relay, hermetically sealed for hazardous locations, 24 VAC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$106
H750-3C-120A	Octal control relay, hermetically sealed for hazardous locations, 120 VAC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$111
H750-3C-240A	Octal control relay, hermetically sealed for hazardous locations, 240 VAC coil voltage, 3PDT, 12A contact rating, 11-pin configuration. Purchase 750-3C-SKT mounting socket separately.	\$111
Product Code	Electromechanical Card Relays and Accessories	Aust\$
RS4N-DE	Card relay (4 included), mounted in socket, 24 VDC coil, SPST, 5A contact rating. TY3 relay remover included.	\$70
RS6N-DE	Card relay (6 included), mounted in socket, 24 VDC coil, SPST, 5A contact rating. TY3 relay remover included.	\$98
RB105-DE	Spare relays for the RS series relays, 24 VDC coil, SPST, 5A contact rating, package of 10	\$65
RZ4N	Terminal guard for RS series relays, package of 10	\$40
TY3	Relay remover for RS series relays, package of 10	\$20
Product Code	Power Relays	Aust\$
AD-PR40-1C-12D	Power relay, 12 VDC coil voltage, SPDT, 40A contact rating, open style panel mount	\$33
AD-PR40-1C-24D	Power relay, 24 VDC coil voltage, SPDT, 40A contact rating, open style panel mount	\$35
AD-PR40-1C-24A	Power relay, 24 VAC coil voltage, SPDT, 40A contact rating, open style panel mount	\$40
AD-PR40-1C-120A	Power relay, 120 VAC coil voltage, SPDT, 40A contact rating, open style panel mount	\$36
AD-PR40-1C-240A	Power relay, 240 VAC coil voltage, SPDT, 40A contact rating, open style panel mount	\$41
AD-PR40-2A-12D	Power relay, 12 VDC coil voltage, DPST normally open, 40A contact rating, open style panel mount	\$39
AD-PR40-2A-24D	Power relay, 24 VDC coil voltage, DPST normally open, 40A contact rating, open style panel mount	\$39
AD-PR40-2A-24A	Power relay, 24 VAC coil voltage, DPST normally open, 40A contact rating, open style panel mount	\$38
AD-PR40-2A-120A	Power relay, 120 VAC coil voltage, DPST normally open, 40A contact rating, open style panel mount	\$38
AD-PR40-2A-240A	Power relay, 240 VAC coil voltage, DPST normally open, 40A contact rating, open style panel mount	\$39
AD-PR40-2C-12D	Power relay, 12 VDC coil voltage, DPDT, 40A contact rating, open style panel mount	\$42
AD-PR40-2C-24D	Power relay, 24 VDC coil voltage, DPDT, 40A contact rating, open style panel mount	\$43
AD-PR40-2C-24A	Power relay, 24 VAC coil voltage, DPDT, 40A contact rating, open style panel mount	\$43
AD-PR40-2C-120A	Power relay, 120 VAC coil voltage, DPDT, 40A contact rating, open style panel mount	\$43

AD-PR40-2C-240A	Power relay, 240 VAC coil voltage, DPDT, 40A contact rating, open style panel mount	\$43
Product Code	Solid State DIN Mount General Purpose Relays (10-25A)	Aust\$
AD-SSR210-AC	Solid state DIN-rail mount relay, 90-280 VAC coil voltage, 24-280 VAC load voltage, 10A contact rating. Finger-safe design and LED status lamp.	\$88
AD-SSR225-AC	Solid state DIN-rail mount relay, 90-280 VAC coil voltage, 24-280 VAC load voltage, 25A contact rating. Finger-safe design and LED status lamp.	\$102
AD-SSR810-AC-28Z	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$55
AD-SSR810-AC-28R	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$61
AD-SSR810-DC-28Z	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$46
AD-SSR810-DC-28R	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$46
AD-SSR810-DC-28RN	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally closed SCR, 10A contact rating, 24-280 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$49
AD-SSR810-AC-48Z	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$55
AD-SSR810-AC-48R	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$70
AD-SSR810-DC-48Z	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$47
AD-SSR810-DC-48R	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$51
AD-SSR810-AC-60Z	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$70
AD-SSR810-AC-60R	Solid state relay, 35mm DIN-rail mount, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$73
AD-SSR810-DC-60Z	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$54
AD-SSR810-DC-60R	Solid state relay, 35mm DIN-rail mount, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, random cross. Finger-safe design and LED status lamp.	\$54

Product Code	Solid State Hockey Puck Style Panel Mount Relays (10-75A) and Accessories	Aust\$
AD-SSR610-AC-280A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$40
AD-SSR610-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$36
AD-SSR6T10-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$36
AD-SSR625-AC-280A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 25A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$52
AD-SSR625-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 25A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$39
AD-SSR6T25-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 25A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$41
AD-SSR640-AC-280A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 40A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$55
AD-SSR640-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 40A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$54
AD-SSR6T40-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 40A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$51
AD-SSR650-AC-280A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 50A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$65
AD-SSR650-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 50A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$65
AD-SSR675-AC-280A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 75A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$90
AD-SSR675-DC-280A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 75A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$90
AD-SSR6M12-DC-200D	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open MOSFET, 12A contact rating, 3-200 VDC load voltage, DC switching. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$38
AD-SSR6M25-DC-200D	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open MOSFET, 25A contact rating, 3-200 VDC load voltage, DC switching. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$88
AD-SSR6M40-DC-200D	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open MOSFET, 40A contact rating, 3-200 VDC load voltage, DC switching. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$88
AD-SSR610-AC-480A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$33
AD-SSR610-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$33
AD-SSR6T10-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$33
AD-SSR625-AC-480A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 25A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$41
AD-SSR625-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 25A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$39
AD-SSR6T25-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 25A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$42
AD-SSR640-AC-480A	Solid state relay, panel mount, hockey puck style, 90-280 VAC input voltage, SPST, normally open SCR, 40A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$70
AD-SSR640-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open SCR, 40A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$65
AD-SSR6T40-DC-480A	Solid state relay, panel mount, hockey puck style, 3-32 VDC input voltage, SPST, normally open TRIAC, 40A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp. Includes thermal mounting pad.	\$51
AD-SSR-THERM-PAD	Thermal mounting pad for solid state relays starting with AD-SSR6, 10 per package	\$40

Product Code	Solid State DIN Mount Hazardous Location Relays (8-15A)	Aust\$
AD-HSSR815-DC-05	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 3.5-32 VDC input voltage, SPST, normally open MOSFET, 15A contact rating, 3-50 VDC load voltage, DC switching. Finger-safe design and LED status lamp.	\$124
AD-HSSR808-DC-15	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 3.5-32 VDC input voltage, SPST, normally open MOSFET, 8A contact rating, 3-150 VDC load voltage, DC switching. Finger-safe design and LED status lamp.	\$121
AD-HSSR810-AC-28	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$121
AD-HSSR810-DC-28	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 24-280 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$119
AD-HSSR810-AC-48	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$124
AD-HSSR810-DC-48	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-480 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$121
AD-HSSR810-AC-60	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 90-280 VAC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$128
AD-HSSR810-DC-60	Solid state relay, 35mm DIN-rail mount, hazardous location certified, 3-32 VDC input voltage, SPST, normally open SCR, 10A contact rating, 48-600 VAC load voltage, zero cross. Finger-safe design and LED status lamp.	\$124
Product Code	Solid State Socket Mount Relays (4A)	Aust\$
AD-70S2-04B	Solid state relay, plug-in, 3-30 VDC input voltage, SPST, normally open TRIAC, 4A contact rating, 24-140 VAC load voltage, zero cross. Purchase 782-2C-SKT mounting socket separately.	\$44
AD-70S2-04C	Solid state relay, plug-in, 3-30 VDC input voltage, SPST, normally open TRIAC, 4A contact rating, 24-280 VAC load voltage, zero cross. Purchase 782-2C-SKT mounting socket separately.	\$44
AD-70S2-04D	Solid state relay, plug-in, 3-30 VDC input voltage, SPST, normally open TRIAC, 4A contact rating, 8-50 VAC load voltage, zero cross. Purchase 782-2C-SKT mounting socket separately.	\$44
Product Code	Counter/Timer/Tach	Aust\$
CTT-AN-D24	Multi-function digital counter / timer / tachometer, operates in one of four modes (selectable) - Counter (5 functions), Timer (12 functions), mixed Timer + Counter, or Tachometer. 1/16 DIN housing, double-line, 6-digit, two-color LCD display, 24VDC power	\$158
CTT-AN-A120	Multi-function digital counter / timer / tachometer, operates in one of four modes (selectable) - Counter (5 functions), Timer (12 functions), mixed Timer + Counter, or Tachometer. 1/16 DIN housing, double-line, 6-digit, two-color LCD display, 100-240 VAC	\$158
CTT-1C-D24	Multi-function digital counter / timer / tachometer, operates in one of four modes (selectable) - Counter (5 functions), Timer (12 functions), mixed Timer + Counter, or Tachometer. 1/16 DIN housing, double-line, 6-digit, two-color LCD display, 24VDC power	\$158
CTT-1C-A120	Multi-function digital counter / timer / tachometer, operates in one of four modes (selectable) - Counter (5 functions), Timer (12 functions), mixed Timer + Counter, or Tachometer. 1/16 DIN housing, double-line, 6-digit, two-color LCD display, 100-240 VAC	\$158
Product Code	FUJI Timer Relays and Accessories	Aust\$
MS4SM-AP-ADC	Multi-mode timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately.	\$113
MS4SA-AP-ADC	On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately.	\$113
MS4SC-AP-ADC	On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 100-240 VAC input power. SPDT timed relay output and SPDT instant relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately.	\$113
MS4SM-CE-ADC	Multi-mode timer with selectable timing range from 0.05 seconds to 60 hours, 24 VDC/VAC input power, DPDT relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately.	\$113
MS4SA-CE-ADC	Fuji Electric on-delay timer, 0.05 seconds to 60 hours selectable timing range, 24 VAC/VDC operating voltage, Output 1: DPDT relay.	\$113
MS4SC-CE-ADC	On-delay timer with selectable timing range from 0.05 seconds to 60 hours, 24 VDC/VAC input power, SPDT timed relay output and SPDT instant relay output. Socket mounts not included (purchase separately). For through-door mounting, purchase panel clips PANEL-16 separately.	\$105
ST7P-2A15S-ADC	Mini-DIN on-delay timer with timing range of 0.4 seconds to 5 seconds, 100-120 VAC input power, DPDT relay output	\$87
ST7P-2A13T-ADC	Mini-DIN on-delay timer with timing range of 2 seconds to 30 seconds, 100-120 VAC input power, DPDT relay output	\$87
ST7P-2A16T-ADC	Mini-DIN on-delay timer with timing range of 4 seconds to 60 seconds, 100-120 VAC input power, DPDT relay output	\$87
ST7P-2A11N-ADC	Mini-DIN on-delay timer with timing range of 1 min. to 10 min., 100-120 VAC input power, DPDT relay output	\$87
ST7P-2A16N-ADC	Mini-DIN on-delay timer with timing range of 4 min. to 60 min., 100-120 VAC input power, DPDT relay output	\$87
ST7P-2DE5S-ADC	Mini-DIN on-delay timer with timing range of 0.4 seconds to 5 seconds, 24 VDC input power, DPDT relay output	\$87
ST7P-2DE3T-ADC	Mini-DIN on-delay timer with timing range of 2 seconds to 30 seconds, 24 VDC input power, DPDT relay output	\$87
ST7P-2DE6T-ADC	Mini-DIN on-delay timer with timing range of 4 seconds to 60 seconds, 24 VDC input power, DPDT relay output	\$87

ST7P-2DE1N-ADC	Mini-DIN on-delay timer with timing range of 1 min. to 10 min., 24 VDC input power, DPDT relay output	\$85
ST7P-2DE6N-ADC	Mini-DIN on-delay timer with timing range of 4 min. to 60 min., 24 VDC input power, DPDT relay output	\$85
TP411X	DIN rail mounting socket for MS4SM series timers	\$17
TP48X	DIN rail mounting socket for MS4SA and MS4SC series timers	\$17
TP88X2	DIN rail mounting socket for ST7P series timers	\$17
TP411SBA	Panel mounting socket for MS4SM series timers	\$17
TP48SB	Panel mounting socket for MS4SA and MS4SC series timers	\$17
PANEL-16	Mounting clips for 1/16th DIN timers and temperature/process controllers, 5 clips per package	\$27