

HMI - Operator Panels		
ViewMarq Message Displays		
Product Code	ViewMarq Message Displays	Aust\$
MD4-0112T	ViewMarq industrial LED message display, 1 line by 12 characters, tri-color, 50mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$659
MD4-0124T	ViewMarq industrial LED message display, 1 line by 24 characters, tri-color, 50mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$979
MD4-0212T	ViewMarq industrial LED message display, 2 line by 12 characters, tri-color, 120mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$985
MD4-0224T	ViewMarq industrial LED message display, 2 line by 24 characters, tri-color, 120mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$1,425
MD4-0412T	ViewMarq industrial LED message display, 4 line by 12 characters, tri-color, 241mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$1,419
MD4-0424T	ViewMarq industrial LED message display, 4 line by 24 characters, tri-color, 241mm maximum character size. Supports red, amber and green characters, embedded string and numeric variables, scrolling (right, left, up and down). Includes (1) RS-232 port, (1) RS-485 port and (1) 10/100 BaseT Ethernet port for configuration and external message control; supports serial ASCII, Modbus RTU, and Modbus TCP protocols. equiv. IP66 / IP54 (Indoor only) extruded aluminum housing. UL 508 listed, CE marked. Includes wall mount and chain mount bracket assemblies, cable glands for input wiring and one Ethernet patch cable. Requires configuration software (MD-PGMSW) which can be purchased on CD or downloaded for free.	\$2,475
MD-PGMSW	ViewMarq LED message display Windows-based configuration software, CD includes software and documentation. Windows XP (Service Pack 3), Vista or Windows 7 (32 and 64-bit) supported. Requires serial or Ethernet connection to ViewMarq Display. Order programming cable(s) separately. Also available for free download online at <a href="http://www.automationdirect.com/pn/md-pgmsw">www.automationdirect.com/pn/md-pgmsw</a> .	\$22
MD-USER-M	Hardware/Software user manual for ViewMarq message display units. Available only as a free download from Automationdirect Web site.	<b>Free Download</b>
MD-BRK-1	Replacement wall mounting bracket assemblies for ViewMarq message display units, 2 per pack.	\$44
MD-BRK-2	Replacement chain mount brackets for ViewMarq message display units, 2 per pack.	\$22
MD-PWR-COV	Replacement power connection cover for ViewMarq message display units. Includes (1) cover and (1) 1/2 inch NPT cord grip.	\$44
MD-COM-COV	Replacement communications cover for ViewMarq message display units. Includes (1) cover and (2) 1/2 inch NPT and (1) 3/4 inch NPT with 6mm and 10mm hole plugs.	\$28
MD-TERM-SET	Replacement terminal block set for ViewMarq message display units. Includes (1) 2-terminal DC power connector, (1) 3-terminal AC power connector, (1) 10-terminal discrete input connector, and (1) 6-terminal serial communications connector.	\$22