



# Connection Cables

Please note: \$US prices shown  
For current \$AUD visit [www.directautomation.com.au](http://www.directautomation.com.au)

| ZIPLink Connection Cables               |                                                                                                                                                          |                   |              |         |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                             | Description                                                                                                                                              | Insulation Rating | Weight (lbs) | Price   |
| <b>BRX ZIPLink Cables</b>               |                                                                                                                                                          |                   |              |         |
| <a href="#"><u>ZL-BX-CBL15</u></a>      | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with BRX 18-point and 36-point PLCs.             | 300V, 80°C        | 0.3          | \$30.50 |
| <a href="#"><u>ZL-BX-CBL15-1</u></a>    | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with BRX 18-point and 36-point PLCs.               | 300V, 80°C        | 0.4          | \$35.50 |
| <a href="#"><u>ZL-BX-CBL15-2</u></a>    | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with BRX 18-point and 36-point PLCs.               | 300V, 80°C        | 0.7          | \$28.50 |
| <a href="#"><u>ZL-BX-CBL15-1P</u></a>   | ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 3.2ft/1m cable length. For use with BRX 18-point and 36-point PLCs.                        | 300V, 80°C        | 0.4          | \$24.50 |
| <a href="#"><u>ZL-BX-CBL15-2P</u></a>   | ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 6.5ft/2m cable length. For use with BRX 18-point and 36-point PLCs.                        | 300V, 80°C        | 0.6          | \$25.50 |
| <a href="#"><u>ZL-BX-CBL20</u></a>      | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with BRX 10-point PLCs.                          | 300V, 80°C        | 0.3          | \$23.50 |
| <a href="#"><u>ZL-BX-CBL20-1</u></a>    | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with BRX 10-point PLCs.                            | 300V, 80°C        | 0.5          | \$25.50 |
| <a href="#"><u>ZL-BX-CBL20-2</u></a>    | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with BRX 10-point PLCs.                            | 300V, 80°C        | 0.7          | \$31.00 |
| <a href="#"><u>ZL-BX-CBL20-1P</u></a>   | ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 3.2ft/1m cable length. For use with BRX 10-point PLCs.                                     | 300V, 80°C        | 0.4          | \$21.50 |
| <a href="#"><u>ZL-BX-CBL20-2P</u></a>   | ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 6.5ft/2m cable length. For use with BRX 10-point PLCs.                                     | 300V, 80°C        | 0.7          | \$28.50 |
| <a href="#"><u>ZL-BX-CBL40-S</u></a>    | ZIPLink PLC I/O cable, 40-pin connector to 40-pin connector, shielded, 1.6ft/0.5m cable length. For use with BRX series high-speed modules.              | 300V, 80°C        | 0.5          | \$35.00 |
| <a href="#"><u>ZL-BX-CBL40-1S</u></a>   | ZIPLink PLC I/O cable, 40-pin connector to 40-pin connector, shielded, 3.2ft/1m cable length. For use with BRX series high-speed modules.                | 300V, 80°C        | 0.7          | \$43.50 |
| <a href="#"><u>ZL-BXEM-CBL10</u></a>    | ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with BRX 8-point expansion modules.              | 300V, 80°C        | 0.3          | \$18.00 |
| <a href="#"><u>ZL-BXEM-CBL10-1</u></a>  | ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with BRX 8-point expansion modules.                | 300V, 80°C        | 0.4          | \$21.50 |
| <a href="#"><u>ZL-BXEM-CBL10-2</u></a>  | ZIPLink PLC I/O cable, 10-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with BRX 8-point expansion modules.                | 300V, 80°C        | 0.7          | \$24.50 |
| <a href="#"><u>ZL-BXEM-CBL10-1P</u></a> | ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 3.2ft/1m cable length. For use with BRX 8-point expansion modules.                         | 300V, 80°C        | 0.4          | \$18.00 |
| <a href="#"><u>ZL-BXEM-CBL10-2P</u></a> | ZIPLink PLC I/O cable, 10-position terminal block to pigtail, 6.5ft/2m cable length. For use with BRX 8-point expansion modules.                         | 300V, 80°C        | 0.6          | \$24.00 |
| <a href="#"><u>ZL-BXEM-CBL15</u></a>    | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with BRX 5-point and 12-point expansion modules. | 300V, 80°C        | 0.3          | \$20.50 |
| <a href="#"><u>ZL-BXEM-CBL15-1</u></a>  | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with BRX 5-point and 12-point expansion modules.   | 300V, 80°C        | 0.5          | \$21.00 |
| <a href="#"><u>ZL-BXEM-CBL15-2</u></a>  | ZIPLink PLC I/O cable, 15-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with BRX 5-point and 12-point expansion modules.   | 300V, 80°C        | 0.7          | \$26.50 |
| <a href="#"><u>ZL-BXEM-CBL15-1P</u></a> | ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 3.2ft/1m cable length. For use with BRX 5-point and 12-point expansion modules.            | 300V, 80°C        | 0.4          | \$20.00 |
| <a href="#"><u>ZL-BXEM-CBL15-2P</u></a> | ZIPLink PLC I/O cable, 15-position terminal block to pigtail, 6.5ft/2m cable length. For use with BRX 5-point and 12-point expansion modules.            | 300V, 80°C        | 0.7          | \$23.00 |
| <a href="#"><u>ZL-BXEM-CBL20</u></a>    | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 1.6ft/0.5m cable length. For use with BRX 16-point expansion modules.             | 300V, 80°C        | 0.3          | \$30.50 |
| <a href="#"><u>ZL-BXEM-CBL20-1</u></a>  | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 3.2ft/1m cable length. For use with BRX 16-point expansion modules.               | 300V, 80°C        | 0.5          | \$29.00 |
| <a href="#"><u>ZL-BXEM-CBL20-2</u></a>  | ZIPLink PLC I/O cable, 20-position terminal block to 24-pin connector, 6.5ft/2m cable length. For use with BRX 16-point expansion modules.               | 300V, 80°C        | 0.7          | \$36.00 |
| <a href="#"><u>ZL-BXEM-CBL20-1P</u></a> | ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 3.2ft/1m cable length. For use with BRX 16-point expansion modules.                        | 300V, 80°C        | 0.4          | \$30.50 |
| <a href="#"><u>ZL-BXEM-CBL20-2P</u></a> | ZIPLink PLC I/O cable, 20-position terminal block to pigtail, 6.5ft/2m cable length. For use with BRX 16-point expansion modules.                        | 300V, 80°C        | 0.7          | \$31.50 |

**ZL-BX-CBL15****ZL-BX-CBL20-1P****ZL-BXEM-CBL20****ZL-BXEM-CBL20-1P**



# Connection Cables (cont.)

| ZIPLink Connection Cables               |                                                                                                 |                   |              |         |
|-----------------------------------------|-------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                             | Description                                                                                     | Insulation Rating | Weight (lbs) | Price   |
| <i>BRX ZIPLink Cables, continued</i>    |                                                                                                 |                   |              |         |
| <a href="#"><u>ZL-D24-CBL40</u></a>     | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.36         | \$40.50 |
| <a href="#"><u>ZL-D24-CBL40-1</u></a>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.56         | \$47.50 |
| <a href="#"><u>ZL-D24-CBL40-2</u></a>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.61         | \$62.00 |
| <a href="#"><u>ZL-D24-CBL40-X</u></a>   | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m)  | 300V, 80°C        | 0.36         | \$62.00 |
| <a href="#"><u>ZL-D24-CBL40-1X</u></a>  | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG 3.3 ft. (1.0 m)   | 300V, 80°C        | 0.56         | \$71.00 |
| <a href="#"><u>ZL-D24-CBL40-1P</u></a>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.56         | \$43.50 |
| <a href="#"><u>ZL-D24-CBL40-2P</u></a>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)  | 300V, 80°C        | 0.61         | \$59.00 |
| <a href="#"><u>ZL-D24-CBL40-2XP</u></a> | Cable w/45° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)   | 300V, 80°C        | 0.61         | \$80.00 |



**ZL-D24-CBL40**



**ZL-D24-CBL40-1P**



**ZL-D24-CBL40-1XP**



# Connection Cables (cont.)

| ZIPLink Connection Cables             |                                                                                                                                                                                                                                     |                   |              |         |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                           | Description                                                                                                                                                                                                                         | Insulation Rating | Weight (lbs) | Price   |
| <b>CLICK ZIPLink Cables</b>           |                                                                                                                                                                                                                                     |                   |              |         |
| <a href="#"><u>ZL-C0-CBL11</u></a>    | Cable for module with 11 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                                                     | 300V, 80°C        | 0.21         | \$28.50 |
| <a href="#"><u>ZL-C0-CBL11-1</u></a>  | Cable for module with 11 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                     | 300V, 80°C        | 0.31         | \$31.50 |
| <a href="#"><u>ZL-C0-CBL11-2</u></a>  | Cable for module with 11 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                     | 300V, 80°C        | 0.56         | \$37.00 |
| <a href="#"><u>ZL-C0-CBL11-1P</u></a> | Cable for module with 11 terminals to pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                              | 300V, 80°C        | 0.21         | \$28.50 |
| <a href="#"><u>ZL-C0-CBL11-2P</u></a> | Cable for module with 11 terminals to pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                              | 300V, 80°C        | 0.26         | \$34.50 |
| <a href="#"><u>ZL-C0-CBL20</u></a>    | Cable for module with 20 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                                                     | 300V, 80°C        | 0.25         | \$31.50 |
| <a href="#"><u>ZL-C0-CBL20-1</u></a>  | Cable for module with 20 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                     | 300V, 80°C        | 0.31         | \$35.00 |
| <a href="#"><u>ZL-C0-CBL20-2</u></a>  | Cable for module with 20 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                     | 300V, 80°C        | 0.61         | \$42.50 |
| <a href="#"><u>ZL-C0-CBL20-1P</u></a> | Cable for module with 20 terminals to pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                              | 300V, 80°C        | 0.21         | \$31.50 |
| <a href="#"><u>ZL-C0-CBL20-2P</u></a> | Cable for module with 20 terminals to pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                              | 300V, 80°C        | 0.26         | \$39.50 |
| <b>DL05 and DL06 ZIPLink Cables</b>   |                                                                                                                                                                                                                                     |                   |              |         |
| <a href="#"><u>ZL-D0-CBL13</u></a>    | Cable for module with 13 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                                                     | 300V, 80°C        | 0.26         | \$24.50 |
| <a href="#"><u>ZL-D0-CBL24</u></a>    | Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                                                 | 300V, 80°C        | 0.26         | \$29.00 |
| <a href="#"><u>ZL-D0-CBL24-1</u></a>  | Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                 | 300V, 80°C        | 0.36         | \$31.50 |
| <a href="#"><u>ZL-D0-CBL24-2</u></a>  | Cable for module with 24-pin connector to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                 | 300V, 80°C        | 0.56         | \$40.00 |
| <a href="#"><u>ZL-D0-CBL24-L</u></a>  | Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                                  | 300V, 80°C        | 0.26         | \$29.50 |
| <a href="#"><u>ZL-D0-CBL24-1L</u></a> | Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                  | 300V, 80°C        | 0.36         | \$31.50 |
| <a href="#"><u>ZL-D0-CBL24-2L</u></a> | Cable for module with 24-pin connector to 24-pin connector for LED module, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                  | 300V, 80°C        | 0.56         | \$40.00 |
| <a href="#"><u>ZL-D0-CBL24-1P</u></a> | Cable for module with 24-pin connector to 24-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                                                  | 300V, 80°C        | 0.26         | \$24.50 |
| <a href="#"><u>ZL-D0-CBL24-2P</u></a> | Cable for module with 24-pin connector to 24-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                                                  | 300V, 80°C        | 0.56         | \$30.50 |
| <a href="#"><u>ZL-D06X-CBL20</u></a>  | Cable used to connect DirectLOGIC 06 PLC fixed inputs with 20 terminals to the <a href="#"><u>ZL-RTB20</u></a> ZIPLink module with a 24-pin connector, can be used on the input side terminal block only, 24 AWG, 1.6 ft. (0.5 m)   | 300V, 80°C        | 0.36         | \$54.00 |
| <a href="#"><u>ZL-D06Y-CBL20</u></a>  | Cable used to connect DirectLOGIC 06 PLC fixed outputs with 20 terminals to the <a href="#"><u>ZL-RTB20</u></a> ZIPLink module with a 24-pin connector, can be used on the output side terminal block only, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.36         | \$44.50 |

**[ZL-C0-CBL11](#)****[ZL-D0-CBL24-1](#)****[ZL-D0-CBL24-1P](#)**



# Connection Cables (cont.)

| ZIPLink Connection Cables               |                                                                                                 |                   |              |         |
|-----------------------------------------|-------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                             | Description                                                                                     | Insulation Rating | Weight (lbs) | Price   |
| <i>Do-more / DL205 ZIPLink Cables</i>   |                                                                                                 |                   |              |         |
| <a href="#"><u>ZL-D2-CBL10</u></a>      | Cable for module with 10 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                 | 300V, 80°C        | 0.36         | \$31.00 |
| <a href="#"><u>ZL-D2-CBL10-1</u></a>    | Cable for module with 10 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                 | 300V, 80°C        | 0.61         | \$34.50 |
| <a href="#"><u>ZL-D2-CBL10-2</u></a>    | Cable for module with 10 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                 | 300V, 80°C        | 0.61         | \$42.50 |
| <a href="#"><u>ZL-D2-CBL10-1P</u></a>   | Cable for module with 10 terminals to pigtail, 24 AWG, 3.3 ft. (1.0 m)                          | 300V, 80°C        | 0.31         | \$33.00 |
| <a href="#"><u>ZL-D2-CBL10-2P</u></a>   | Cable for module with 10 terminals to pigtail, 24 AWG, 6.6 ft. (2.0 m)                          | 300V, 80°C        | 0.46         | \$39.50 |
| <a href="#"><u>ZL-D2-CBL19</u></a>      | Cable for module with 19 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                 | 300V, 80°C        | 0.36         | \$55.00 |
| <a href="#"><u>ZL-D2-CBL19-1</u></a>    | Cable for module with 19 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                 | 300V, 80°C        | 0.61         | \$59.00 |
| <a href="#"><u>ZL-D2-CBL19-2</u></a>    | Cable for module with 19 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                 | 300V, 80°C        | 0.61         | \$64.00 |
| <a href="#"><u>ZL-D2-CBL19-1P</u></a>   | Cable for module with 19 terminals to pigtail, 24 AWG, 3.3 ft. (1.0 m)                          | 300V, 80°C        | 0.61         | \$50.00 |
| <a href="#"><u>ZL-D2-CBL19-2P</u></a>   | Cable for module with 19 terminals to pigtail, 24 AWG, 6.6 ft. (2.0 m)                          | 300V, 80°C        | 0.61         | \$58.00 |
| <a href="#"><u>ZL-D24-CBL40</u></a>     | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.36         | \$40.50 |
| <a href="#"><u>ZL-D24-CBL40-1</u></a>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.61         | \$47.50 |
| <a href="#"><u>ZL-D24-CBL40-2</u></a>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.61         | \$62.00 |
| <a href="#"><u>ZL-D24-CBL40-X</u></a>   | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m)  | 300V, 80°C        | 0.36         | \$62.00 |
| <a href="#"><u>ZL-D24-CBL40-1X</u></a>  | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.61         | \$71.00 |
| <a href="#"><u>ZL-D24-CBL40-1P</u></a>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.56         | \$43.50 |
| <a href="#"><u>ZL-D24-CBL40-2P</u></a>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)  | 300V, 80°C        | 0.61         | \$59.00 |
| <a href="#"><u>ZL-D24-CBL40-2XP</u></a> | Cable w/45° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)   | 300V, 80°C        | 0.61         | \$80.00 |
| <a href="#"><u>ZL-D24-CON</u></a>       | ZIPLink solder-style connector, 180°, 40-pin, qty. 2                                            | N/A               | 0.36         | \$47.00 |
| <a href="#"><u>ZL-D24-CON-X</u></a>     | ZIPLink solder-style connector, 105°, 40-pin, qty. 2                                            | N/A               | 0.36         | \$89.00 |

**ZL-D06X-CBL20****ZL-D2-CBL10****ZL-D24-CBL40****ZL-D2-CBL19-1P**



# Connection Cables (cont.)

| ZIPLink Connection Cables      |                                                                                                 |                   |              |         |
|--------------------------------|-------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                    | Description                                                                                     | Insulation Rating | Weight (lbs) | Price   |
| <b>DL405 ZIPLink Cables</b>    |                                                                                                 |                   |              |         |
| <b><u>ZL-D24-CBL40</u></b>     | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.36         | \$40.50 |
| <b><u>ZL-D24-CBL40-1</u></b>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.56         | \$47.50 |
| <b><u>ZL-D24-CBL40-2</u></b>   | Cable w/180° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.61         | \$62.00 |
| <b><u>ZL-D24-CBL40-X</u></b>   | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m)  | 300V, 80°C        | 0.36         | \$62.00 |
| <b><u>ZL-D24-CBL40-1X</u></b>  | Cable w/45° plug for module with 40-pin connector to 40-pin connector, 24 AWG 3.3 ft. (1.0 m)   | 300V, 80°C        | 0.56         | \$71.00 |
| <b><u>ZL-D24-CBL40-1P</u></b>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.56         | \$43.50 |
| <b><u>ZL-D24-CBL40-2P</u></b>  | Cable w/180° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)  | 300V, 80°C        | 0.61         | \$59.00 |
| <b><u>ZL-D24-CBL40-2XP</u></b> | Cable w/45° plug for module with 40-pin connector to 40-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)   | 300V, 80°C        | 0.61         | \$80.00 |
| <b><u>ZL-D24-CON</u></b>       | ZIPLink solder-style connector, 180°, 40-pin, qty. 2                                            | N/A               | 0.36         | \$47.00 |
| <b><u>ZL-D24-CON-X</u></b>     | ZIPLink solder-style connector, 45°, 40-pin, qty. 2                                             | N/A               | 0.36         | \$89.00 |



**ZL-D24-CBL40-1P**



**ZL-D24-CBL40-1XP**



**ZL-D24-CON Parts**



# Connection Cables (cont.)

| ZIPLink Connection Cables                  |                                                                                           |                   |              |         |
|--------------------------------------------|-------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                                | Description                                                                               | Insulation Rating | Weight (lbs) | Price   |
| <b>Productivity1000 ZIPLink Cables</b>     |                                                                                           |                   |              |         |
| <a href="#"><u>ZL-P1-CBL10</u></a>         | Cable for module with 10 terminals to 24-pin 90-degree connector, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.26         | \$25.50 |
| <a href="#"><u>ZL-P1-CBL10-1</u></a>       | Cable for module with 10 terminals to 24-pin 90-degree connector, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.38         | \$25.50 |
| <a href="#"><u>ZL-P1-CBL10-2</u></a>       | Cable for module with 10 terminals to 24-pin 90-degree connector, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.63         | \$29.50 |
| <a href="#"><u>ZL-P1-CBL10-1P</u></a>      | Cable for module with 10 terminals connector to 20-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.31         | \$21.00 |
| <a href="#"><u>ZL-P1-CBL10-2P</u></a>      | Cable for module with 10 terminals connector to 20-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)  | 300V, 80°C        | 0.56         | \$23.00 |
| <a href="#"><u>ZL-P1-CBL18</u></a>         | Cable for module with 18 terminals to 24-pin 90-degree connector, 24 AWG, 1.6 ft. (0.5 m) | 300V, 80°C        | 0.28         | \$27.00 |
| <a href="#"><u>ZL-P1-CBL18-1</u></a>       | Cable for module with 18 terminals to 24-pin 90-degree connector, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.41         | \$27.00 |
| <a href="#"><u>ZL-P1-CBL18-2</u></a>       | Cable for module with 18 terminals to 24-pin 90-degree connector, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.66         | \$29.00 |
| <a href="#"><u>ZL-P1-CBL18-1P</u></a>      | Cable for module with 18 terminals connector to 20-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)  | 300V, 80°C        | 0.33         | \$20.50 |
| <a href="#"><u>ZL-P1-CBL18-2P</u></a>      | Cable for module with 18 terminals connector to 20-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)  | 300V, 80°C        | 0.58         | \$23.00 |
| <b>Serial Communication ZIPLink Cables</b> |                                                                                           |                   |              |         |
| <a href="#"><u>ZL-RJ12-CBL-2</u></a>       | Crossover cable with 6-pin RJ12 to 6-pin RJ12 connectors, 26 AWG, 6.6 ft. (2.0 m)         | 150V, 60°C        | 0.26         | \$6.75  |
| <a href="#"><u>ZL-RJ12-CBL-2P</u></a>      | Cable with 6-pin RJ12 connector to 6-wire pigtail, 26 AWG, 6.6 ft. (2.0 m)                | 150V, 60°C        | 0.26         | \$7.75  |

**[ZL-P1-CBL10-1](#)****[ZL-P1-CBL10-1P](#)****[ZL-RJ12-CBL-2](#)****[ZL-RJ12-CBL-2P](#)****[ZL-P1-CBL18-1](#)****[ZL-P1-CBL18-1P](#)**



# Connection Cables (cont.)

| ZIPLink Connection Cables                  |                                                                                                                                    |                   |              |         |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                                | Description                                                                                                                        | Insulation Rating | Weight (lbs) | Price   |
| <b>Productivity®2000 ZIPLink Cables</b>    |                                                                                                                                    |                   |              |         |
| <b><u>ZL-P2-CBL18</u></b>                  | Cable for module with 18 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                    | 300V, 80°C        | 0.36         | \$32.00 |
| <b><u>ZL-P2-CBL18-1</u></b>                | Cable for module with 18 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                    | 300V, 80°C        | 0.36         | \$35.50 |
| <b><u>ZL-P2-CBL18-2</u></b>                | Cable for module with 18 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                    | 300V, 80°C        | 0.56         | \$50.00 |
| <b><u>ZL-P2-CBL18-1P</u></b>               | Cable for module with 18-pin connector to 20-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                 | 300V, 80°C        | 0.56         | \$31.00 |
| <b><u>ZL-P2-CBL18-2P</u></b>               | Cable for module with 18-pin connector to 20-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                 | 300V, 80°C        | 0.61         | \$43.00 |
| <b><u>ZL-P2-CBL24</u></b>                  | Cable for module with 24 terminals to 24-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                    | 300V, 80°C        | 0.36         | \$43.50 |
| <b><u>ZL-P2-CBL24-1</u></b>                | Cable for module with 24 terminals to 24-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                    | 300V, 80°C        | 0.56         | \$43.50 |
| <b><u>ZL-P2-CBL24-2</u></b>                | Cable for module with 24 terminals to 24-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                    | 300V, 80°C        | 0.61         | \$43.00 |
| <b><u>ZL-P2-CBL24-1P</u></b>               | Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.36         | \$43.50 |
| <b><u>ZL-P2-CBL24-2P</u></b>               | Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.56         | \$43.00 |
| <b><u>ZL-P3-CBL40-1P</u></b>               | ZIPLink PLC I/O cable, for Productivity Modules, 40-pin connector to pigtail, 24 AWG, 1.0 meter (3.3 ft.) length.                  | 300V, 80°C        | 0.56         | \$35.50 |
| <b><u>ZL-P3-CBL40-2P</u></b>               | ZIPLink PLC I/O cable, for Productivity Modules, 40-pin connector to pigtail, 24 AWG, 2.0 meter (6.6 ft.) length.                  | 300V, 80°C        | 0.56         | \$51.00 |
| <b><u>ZL-CBL40-S</u></b>                   | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 1.6 ft. (0.5 m) (High-Speed I/O modules only)        | 300V, 80°C        | 0.4          | \$36.50 |
| <b><u>ZL-CBL40-1S</u></b>                  | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 3.3 ft. (1.0 m) (High-Speed I/O modules only)        | 300V, 80°C        | 0.7          | \$46.50 |
| <b><u>ZL-CBL40-2S</u></b>                  | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 6.6 ft. (2.0 m) (High-Speed I/O modules only)        | 300V, 80°C        | 1.2          | \$61.00 |
| <b>Serial Communication ZIPLink Cables</b> |                                                                                                                                    |                   |              |         |
| <b><u>ZL-RJ12-CBL-2</u></b>                | Crossover cable with 6-pin RJ12 to 6-pin RJ12 connectors, 26 AWG, 6.6 ft. (2.0 m)                                                  | 150V, 60°C        | 0.26         | \$6.75  |
| <b><u>ZL-RJ12-CBL-2P</u></b>               | Cable with 6-pin RJ12 connector to 6-wire pigtail, 26 AWG, 6.6 ft. (2.0 m)                                                         | 150V, 60°C        | 0.26         | \$7.75  |

**ZL-P2-CBL18-1****ZL-P2-CBL18-1P****ZL-RJ12-CBL-2****ZL-RJ12-CBL-2P****ZL-P2-CBL24-1P**



# Connection Cables (cont.)

| ZIPLink Connection Cables                  |                                                                                                                                                                                                |                   |              |         |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                                | Description                                                                                                                                                                                    | Insulation Rating | Weight (lbs) | Price   |
| <b>Productivity3000 ZIPLink Cables</b>     |                                                                                                                                                                                                |                   |              |         |
| <a href="#"><u>ZL-P3-CBL20</u></a>         | Cable for module with 20 terminals to 20-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                                | 300V, 80°C        | 0.36         | \$44.50 |
| <a href="#"><u>ZL-P3-CBL20-1</u></a>       | Cable for module with 20 terminals to 20-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                | 300V, 80°C        | 0.36         | \$53.00 |
| <a href="#"><u>ZL-P3-CBL20-2</u></a>       | Cable for module with 20 terminals to 20-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                | 300V, 80°C        | 0.56         | \$61.00 |
| <a href="#"><u>ZL-P3-CBL20-L</u></a>       | Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 1.6 ft. (0.5 m)                                                                                             | 300V, 80°C        | 0.36         | \$50.00 |
| <a href="#"><u>ZL-P3-CBL20-1L</u></a>      | Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 3.3 ft. (1.0 m)                                                                                             | 300V, 80°C        | 0.36         | \$53.00 |
| <a href="#"><u>ZL-P3-CBL20-2L</u></a>      | Cable for module with 20-pin connector to 20-pin connector for LED module, 24 AWG, 6.6 ft. (2.0 m)                                                                                             | 300V, 80°C        | 0.56         | \$61.00 |
| <a href="#"><u>ZL-P3-CBL20-P</u></a>       | Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 1.6 ft. (0.5 m)                                                                                                             | 300V, 80°C        | 0.36         | \$48.00 |
| <a href="#"><u>ZL-P3-CBL20-1P</u></a>      | Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                                                                             | 300V, 80°C        | 0.56         | \$43.50 |
| <a href="#"><u>ZL-P3-CBL20-2P</u></a>      | Cable for module with 20-pin connector to 20-wire pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                                                                             | 300V, 80°C        | 0.61         | \$53.00 |
| <a href="#"><u>ZL-CBL40</u></a>            | Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 1.6 ft. (0.5 m)                                                                                                            | 300V, 80°C        | 0.36         | \$31.50 |
| <a href="#"><u>ZL-CBL40-1</u></a>          | Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 3.3 ft. (1.0 m)                                                                                                            | 300V, 80°C        | 0.56         | \$37.50 |
| <a href="#"><u>ZL-CBL40-2</u></a>          | Cable for module with 40-pin connector to 40-pin connector, 24 AWG, 6.6 ft. (2.0 m)                                                                                                            | 300V, 80°C        | 0.61         | \$51.00 |
| <a href="#"><u>ZL-CBL40-S</u></a>          | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 1.6 ft. (0.5 m) (High-Speed I/O modules only)                                                                    | 300V, 80°C        | 0.4          | \$36.50 |
| <a href="#"><u>ZL-CBL40-1S</u></a>         | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 3.3 ft. (1.0 m) (High-Speed I/O modules only)                                                                    | 300V, 80°C        | 0.7          | \$46.50 |
| <a href="#"><u>ZL-CBL40-2S</u></a>         | Cable for module with 40-pin connector to 40-pin connector, shielded, 24 AWG, 6.6 ft. (2.0 m) (High-Speed I/O modules only)                                                                    | 300V, 80°C        | 1.2          | \$61.00 |
| <a href="#"><u>ZL-P3-CBL40-1P</u></a>      | Cable for module with 40 terminals to pigtail, 24 AWG, 3.3 ft. (1.0 m)                                                                                                                         | 300V, 80°C        | 0.41         | \$35.50 |
| <a href="#"><u>ZL-P3-CBL40-2P</u></a>      | Cable for module with 40 terminals to pigtail, 24 AWG, 6.6 ft. (2.0 m)                                                                                                                         | 300V, 80°C        | 0.56         | \$51.00 |
| <b>Universal ZIPLink Cables</b>            |                                                                                                                                                                                                |                   |              |         |
| <a href="#"><u>ZL-CBL24-1P</u></a>         | Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 3.3 ft. (1.0 m)                                                             | 300V, 80°C        | 0.36         | \$24.00 |
| <a href="#"><u>ZL-CBL24-2P</u></a>         | Cable with 24-pin connector to 24-wire pigtail for connecting any 24-pin ZIPLink module to another device, 24 AWG, 6.6 ft. (2.0 m)                                                             | 300V, 80°C        | 0.56         | \$30.50 |
| <a href="#"><u>ZL-DB9F-CBL-2P</u></a>      | ZIPLink pigtail cable with 9-pin D-sub female connector, 28 AWG, 2.0 m (6.6 ft) length                                                                                                         | 300V, 80°C        | 0.30         | \$12.00 |
| <a href="#"><u>ZL-DB9F-CBL-5P</u></a>      | ZIPLink pigtail cable with 9-pin D-sub female connector, 28 AWG, 5.0 m (16.4 ft) length                                                                                                        | 300V, 80°C        | 0.30         | \$22.50 |
| <a href="#"><u>ZL-CBL40-1P</u></a>         | Cable that allows the <a href="#"><u>ZL-RTB40</u></a> , <a href="#"><u>ZL-RFU40</u></a> or <a href="#"><u>ZL-LTB32-24-1</u></a> to custom wire to third party devices, 24 AWG, 3.3 ft. (1.0 m) | 300V, 80°C        | 0.41         | \$37.00 |
| <a href="#"><u>ZL-CBL40-2P</u></a>         | Cable that allows the <a href="#"><u>ZL-RTB40</u></a> , <a href="#"><u>ZL-RFU40</u></a> or <a href="#"><u>ZL-LTB32-24-1</u></a> to custom wire to third party devices, 24 AWG, 6.6 ft. (2.0 m) | 300V, 80°C        | 0.56         | \$51.00 |
| <b>Serial Communication ZIPLink Cables</b> |                                                                                                                                                                                                |                   |              |         |
| <a href="#"><u>ZL-DB9-CBL-2</u></a>        | Shielded cable with 9-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0 m)                                                                                                             | 300V, 80°C        | 0.36         | \$10.00 |
| <a href="#"><u>ZL-DB15-CBL-2</u></a>       | Shielded cable with 15-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0 m)                                                                                                            | 300V, 80°C        | 0.56         | \$13.50 |
| <a href="#"><u>ZL-DB25-CBL-2</u></a>       | Shielded cable with 25-pin D-sub male to female connectors, 28 AWG, 6.6 ft. (2.0 m)                                                                                                            | 300V, 80°C        | 0.56         | \$16.00 |
| <a href="#"><u>ZL-RJ12-CBL-2</u></a>       | Crossover cable with 6-pin RJ12 to 6-pin RJ12 connectors, 26 AWG, 6.6 ft. (2.0 m)                                                                                                              | 150V, 60°C        | 0.26         | \$6.75  |
| <a href="#"><u>ZL-RJ12-CBL-2P</u></a>      | Cable with 6-pin RJ12 connector to 6-wire pigtail, 26 AWG, 6.6 ft. (2.0 m)                                                                                                                     | 150V, 60°C        | 0.26         | \$7.75  |

**[ZL-P3-CBL20-1](#)****[ZL-CBL24-1P](#)****[ZL-DB9-CBL-2](#)****[ZL-RJ12-CBL-2](#)****[ZL-DB9F-CBL-2P](#)****[ZL-RJ12-CBL-2P](#)**



# Connection Cables (cont.)

| ZIPLink Connection Cables                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                   |              |         |
|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------|---------|
| Part Number                                                      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                               | Insulation Rating | Weight (lbs) | Price   |
| <b>AC Drive, Servo, Stepper, and Soft Starter ZIPLink Cables</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                   |              |         |
| <a href="#"><u>GS-RJ12-CBL-2</u></a>                             | RS232 cable with 6-pin RJ12 connector to 6-pin RJ12 connector for GS2 Series drives ONLY. 26 AWG, 6.6 ft. (2.0 m)                                                                                                                                                                                                                                                                                                                                         | 300V, 80°C        | 0.26         | \$10.00 |
| <a href="#"><u>GS-485HD15-CBL-2</u></a>                          | RS485 shielded twisted pair cable with 6-pin RJ12 to 15-pin male D-sub connector for all GS Series/DuraPulse drives, 28 AWG, 6.6 ft. (2.0 m)                                                                                                                                                                                                                                                                                                              | 30V, 80°C         | 0.26         | \$11.00 |
| <a href="#"><u>GS-485RJ12-CBL-2</u></a>                          | GS drive communication cable with 6-pin RJ12 connector to 6-pin RJ12 connector, 3-wire straight-through, 26 AWG, 6.6 ft. (2.0 m). Use this cable and a ZL-CDM-RJ12Xxx distribution module to create a plug and play RS-485 network. Connect multiple SureServo amplifiers, Stellar SR44 soft starters, GS series drives, and Durapulse series drives to a PLC via RS-485.                                                                                 | 300V, 80°C        | 0.11         | \$8.50  |
| <a href="#"><u>GS-EDRV-CBL-2</u></a>                             | GS drive communication cable with 6-pin RJ12 connector to 6-pin RJ12 connector, 6-wire straight-through, 26 AWG, 6.6 ft. (2.0 m). Use this cable to connect GS series and Durapulse series drives to the <a href="#"><u>GS-EDRV</u></a> Ethernet communication module.                                                                                                                                                                                    | 150V, 60°C        | 0.11         | \$8.25  |
| <a href="#"><u>GS-ISOCOON-CBL-2</u></a>                          | ZIPLink GS drive cable, 6-pin RJ12 to 5-pin terminal block, 6.5ft/2m cable length. For use with GS series drives and <a href="#"><u>FA-ISOCOON</u></a> converter.                                                                                                                                                                                                                                                                                         | 150V, 60°C        | 0.11         | \$12.00 |
| <a href="#"><u>ZL-SVC-CBL50</u></a>                              | Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a <a href="#"><u>ZL-RTB50</u></a> module, 28 AWG, 1.6 ft. (0.5 m)                                                                                                                                                                                                                                                                                                | 30V, 80°C         | 0.36         | \$48.50 |
| <a href="#"><u>ZL-SVC-CBL50-1</u></a>                            | Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a <a href="#"><u>ZL-RTB50</u></a> module, 28 AWG, 3.3 ft. (1.0 m)                                                                                                                                                                                                                                                                                                | 30V, 80°C         | 0.46         | \$51.00 |
| <a href="#"><u>ZL-SVC-CBL50-2</u></a>                            | Shielded twisted pair cable with 50-pin connectors to connect any SureServo amplifier to a <a href="#"><u>ZL-RTB50</u></a> module, 28 AWG, 6.6 ft. (2.0 m)                                                                                                                                                                                                                                                                                                | 30V, 80°C         | 0.56         | \$58.00 |
| <a href="#"><u>ZL-CBL50-1P</u></a>                               | SureServo cable used to connect any SureServo amplifier to custom wire to third party devices, 28AWG, 3.3 ft. (1.0 m)                                                                                                                                                                                                                                                                                                                                     | 30V, 80°C         | 0.46         | \$53.00 |
| <a href="#"><u>ZL-CBL50-2P</u></a>                               | SureServo cable used to connect any SureServo amplifier to custom wire to third party devices, 28AWG, 6.6 ft. (2.0 m)                                                                                                                                                                                                                                                                                                                                     | 30V, 80°C         | 0.56         | \$57.00 |
| <a href="#"><u>SVC-232RJ12-CBL-2</u></a>                         | RS232 shielded twisted pair cable with 6-pin RJ12 to 6-pin IEEE connector for all SureServo amplifiers, 6.6 ft. (2.0m)                                                                                                                                                                                                                                                                                                                                    | 30V, 80°C         | 0.16         | \$12.50 |
| <a href="#"><u>SVC-485HD15-CBL-2</u></a>                         | ZIPLink servo cable, 15-pin D-sub HD15 male to 6-pin IEEE connector, shielded, twisted pair, RS-485, 6.5ft/2m cable length. For use with SureServo amplifiers.                                                                                                                                                                                                                                                                                            | 30V, 80°C         | 0.26         | \$13.50 |
| <a href="#"><u>SVC-485RJ12-CBL-2</u></a>                         | ZIPLink servo cable, 6-pin RJ12 to 6-pin IEEE connector, shielded, twisted pair, RS-485, 6.5ft/2m cable length. For use with SureServo amplifiers.                                                                                                                                                                                                                                                                                                        | 30V, 80°C         | 0.16         | \$15.00 |
| <a href="#"><u>SVC-485CFG-CBL-2</u></a>                          | ZIPLink servo cable, 6-pin RJ45 to 6-pin IEEE connector, shielded, twisted pair, RS-485, 6.5ft/2m cable length. For use with SureServo amplifiers.                                                                                                                                                                                                                                                                                                        | 30V, 80°C         | 0.16         | \$18.50 |
| <a href="#"><u>STP-232RJ12-CBL-2</u></a>                         | SureStep drive communication cable with 6P4C RJ11 connector to 6-pin RJ12 connector, 3-wire, RS-232, 26 AWG, 6.6 ft. (2.0 m). Use this cable to connect <a href="#"><u>STP-DRV-4850</u></a> or <a href="#"><u>STP-DRV-80100</u></a> stepper drives to a DL05 PLC or a CLICK PLC.                                                                                                                                                                          | 300V, 80°C        | 0.11         | \$10.50 |
| <a href="#"><u>STP-232HD15-CBL-2</u></a>                         | ZIPLink stepper cable, 6P4C RJ11 to 15-pin D-sub HD15 male, shielded, twisted pair, RS-232, 6.5ft/2m cable length. For use with SureStep drives.                                                                                                                                                                                                                                                                                                          | 30V, 80°C         | 0.21         | \$17.00 |
| <a href="#"><u>SR44-485HD15-CBL-2</u></a>                        | ZIPLink soft starter cable, 6-pin RJ45 to 15-pin D-sub HD15 male, shielded, twisted pair, RS-485, 6.5ft/2m cable length. For use with Stellar soft starters.                                                                                                                                                                                                                                                                                              | 30V, 80°C         | 0.21         | \$16.50 |
| <a href="#"><u>SR44-485RJ45-CBL-2</u></a>                        | Stellar SR44 soft starter communication cable with 6-pin RJ45 connector to 6-pin RJ12 connector, 3-wire, RS-485, 26 AWG, 6.6 ft. (2.0 m). Use this cable and a ZL-CDM-RJ12Xxx distribution module to create a plug and play RS-485 network. Connect multiple SureServo amplifiers, Stellar SR44 soft starters (with optional <a href="#"><u>SR44-RS485</u></a> communication adapter), GS series drives, and Durapulse series drives to a PLC via RS-485. | 30V, 80°C         | 0.16         | \$13.50 |

[GS-485HD15-CBL-2](#)[SVC-232RJ12-CBL-2](#)[SVC-485HD15-CBL-2](#)[ZL-SVC-CBL50](#)[ZL-CBL50-1P](#)